

# Technical Data Sheet

Last data update


3/15/2016

9010  
novantadieci®




*Req. space behind the plasterboard*

85mm




*hole on the plasterboard*

185x175mm




*External measures*

180x170mm




*Measures of the light output*

ø120mm



*Height without electrical part*

70mm



*Height including the electrical part*

75mm

## Notes on measures

## General notes

## PASSO

4059-3001

Recessed Spotlight / CRISTALY

Surface finish : CRISTALY

LED 3.5W / 24Vdc / 350lm / 3000°K / CRI85

## Model

|                |                    |
|----------------|--------------------|
| Code           | 4059               |
| Product family | PASSO              |
| Type           | Recessed Spotlight |

## Material/Surface finish

|                |          |
|----------------|----------|
| Code           | 004      |
| Material       | CRISTALY |
| Surface finish | CRISTALY |

## Electrical part

|                    |        |
|--------------------|--------|
| Code               | 3001   |
| Type               | LED    |
| Power              | 3.5W   |
| Tension            | 24Vdc  |
| Light Output       | 350lm  |
| Colour Temperature | 3000°K |
| CRI                | 85     |

|                          |         |
|--------------------------|---------|
| Light Output of the lamp | 248,5lm |
| Dimmable                 | SI      |

|              |                        |
|--------------|------------------------|
| Power Supply | by Remote Power Supply |
| Connection   | 2 PVC cables           |
| Cover        |                        |

## General Data

|                       |                    |
|-----------------------|--------------------|
| Protection Index      | IP20               |
| Isolation Class       | III                |
| Weight [Kg]           | 0,85               |
| Country of production | MADE IN ITALY      |
| Mounting instruction  | 025.316_9010_REV06 |

## Installation

|                  |                 |
|------------------|-----------------|
| Multisize system | NO              |
| Position         | Wall pathmarker |

## Packaging


|                      |                    |
|----------------------|--------------------|
| Type                 | White american Box |
| Measures AxBxH       | 260x260x135mm      |
| Gross Weight [Kg]    | 1,0371             |
| Master carton        | NO                 |
| Quantity of articles |                    |
| Measures AxBxH       |                    |

# Technical Data Sheet

4059-3001

9010  
novantadieci®

## Fotometric Data




|                                 |         |
|---------------------------------|---------|
| <i>Electrical part</i>          | 3001    |
| <i>Power</i>                    | 3.5W    |
| <i>Light Output</i>             | 350lm   |
| <i>Colour Temperature</i>       | 3000°K  |
| <i>CRI</i>                      | 85      |
| <i>Lamp Light Output</i>        | 71%     |
| <i>Light Output of the lamp</i> | 248,5lm |
| <i>Beam Angle</i>               | 32°     |
| <i>Beam Inclination</i>         | 24°     |

|                    |      |         |
|--------------------|------|---------|
| <i>Illuminance</i> | 0.3m | 1422lux |
|                    | 0.5m | 512lux  |
|                    | 1m   | 128lux  |


## Accessories

### Housing Box for Brickwork




|                                |               |
|--------------------------------|---------------|
| <i>Code</i>                    | 023.406       |
| <i>Measures</i>                | 185X175X90mm  |
| <i>Measures of the hole on</i> | 215X205X100mm |

### Standard Power Supply



|                 |             |
|-----------------|-------------|
| <i>Code</i>     | 026.258     |
| <i>Measures</i> | 130x42x23mm |
| <i>Power</i>    | 12W         |
| <i>Input</i>    | 220-240V~W  |
| <i>Output</i>   | 24Vdc       |




|                 |             |
|-----------------|-------------|
| <i>Code</i>     | 026.259     |
| <i>Measures</i> | 167x45x30mm |
| <i>Power</i>    | 36W         |
| <i>Input</i>    | 220-240V~W  |
| <i>Output</i>   | 24Vdc       |




|                 |             |
|-----------------|-------------|
| <i>Code</i>     | 026.260     |
| <i>Measures</i> | 157x54x36mm |
| <i>Power</i>    | 60W         |
| <i>Input</i>    | 220-240V~W  |
| <i>Output</i>   | 24Vdc       |

### Dimmable Power Supply



|                 |                 |
|-----------------|-----------------|
| <i>Code</i>     | 026.219         |
| <i>Measures</i> | 155x51x26mm     |
| <i>Power</i>    | 21,6W           |
| <i>Input</i>    | 220-240V~W      |
| <i>Output</i>   | 24Vdc           |
| <i>Dimmable</i> | PUSH/0-10V/DALI |



|                 |             |
|-----------------|-------------|
| <i>Code</i>     | 026.209     |
| <i>Measures</i> | 125x82x29mm |
| <i>Power</i>    | 60W         |
| <i>Input</i>    | 220-240 V~W |
| <i>Output</i>   | 24Vdc       |
| <i>Dimmable</i> | PUSH/1-10V  |


# Technical Data Sheet

4059-3001

9010  
novantadieci®

## Accessories

### Other Accessories



|             |               |
|-------------|---------------|
| Code        | 099.142       |
| Description | Emergency Kit |
| Notes       |               |