

PRODUCT DATA SHEET

Tolomeo table LED 3000K



DESIGN BY:

Michele De Lucchi , Giancarlo Fassina 2009

MATERIALS:

Tolomeo table LED

3000K

A004800

Aluminium

Design

inch 30.7 inch 25.4

inch 9.1 inch 50 8

inch 48 750 °


aluminium, steel

aluminium, steel

DESCRIPTION:

Using Led technology, the attention must be focused not only on energy consumption and light efficiency, but above all on the quality and quantity of the distribution of the light. In fact the advantage of the Led is that it emits 100% light fl ow into the direct hemisphere, eliminating dispersion and waste in other directions. This means that in order to obtain illuminance of 1250 lux on the work surface, with an incandescent light source a power of 100W is necessary, while with a Led source 10W is sufficient, with a 90% energy saving. Base and cantilevered arms in polished aluminium; diffuser in matt anodised aluminum; joints and supports in polished aluminium. System of spring balancing. 5 direct Led. The code refers to the luminaire's body only

Interchangeable support: table base, clamp, desk fixed support and twin support that allows two indipendent lamp units to be fitted.





+0-

TECHNICAL DATA SHEET

FEATURES

Product name:

Article Code: Colour: Material: Series:

DIMENSIONS


Length:		
Height:		
Base Diameter:		
Max Extension Height:		
Max Extension Length:		
Glow Wire Test:		

LAMPS INCLUDED

Category:	LED COB
Number:	1
Watt:	10W
Color temperature (K):	3000 K
Class:	A

LUMINAIR

Watt:	10W
Voltage:	24V
Luminous Flux (Im):	593lm
CCT:	3000K
Efficiency:	70%
Efficacy:	59lm/W
CRI:	90
Dimmer Typology:	Microswitch Dimmer



COLOUR



ACCESSORIES



TOLOMEO SUPP.TAVOLO FISSO A004200



TOLOMEO MORSETTO A004100



TOLOMEO BASE TV ALL D230 A004030