


SHADOWLINE
LED LINEAR TRACK SYSTEM

DLD CONTRACT











CE F LED IP20

SHADOWLINE
LED LINEAR TRACK SYSTEM

SURFACE MOUNTED TRACK






H.66mm D.37mm

- Aluminium extrusion
- Supplied with black PC extrusion cover & end caps
- In 3 sizes - use hanging kit to suspend from ceiling
- Cut-to-length

Product code	Length
10-TDS	1500mm
20-TDS	2000mm
30-TDS	2500mm

ACCESSORIES - SURFACE MOUNTED TRACK


30-IDS
2 x Steel surface mounted clips




ACCESSORIES - SUSPENSION TRACK

Surface mounted track can be hung from the ceiling using the accesories below:

40-IDS
2 x 1500mm stainless steel hanging kit




50-IDS
2 x 1500mm stainless steel hanging kit,
1 x with power cable



SHADOWLINE
LED LINEAR TRACK SYSTEM

RECESSED TRACK





H.63mm D.37mm Full D.100mm

- Aluminium extrusion
- Supplied with black PC extrusion cover & end caps
- In 3 sizes
- Cut-to-length


Product code	Length
10-RDS	1500mm
20-RDS	2000mm
30-RDS	2500mm

ACCESSORIES

- Connecting corners for surface mounted, suspension and recessed tracks
- Aluminium extrusion


Corners for Surface Mounted / Suspension Track

Surface mounted | Suspension | Vertical corner
40-TDS



102 x 102mm D.37mm


Surface mounted | Suspension | Horizontal corner
50-TDS



89 x 89mm D.37mm


Corners for Recessed Track

Recessed | Vertical corner
40-RDS



100 x 102mm D.37mm Full D.100mm

Recessed | Horizontal corner
50-RDS




120 x 120mm D.37mm


ACCESSORIES

Connectors for Surface Mounted Track

Surface mounted | Straight circuit joint
10-CDS




Surface mounted | Straight circuit joint 2m power cable
20-CDS




Connectors for Recessed Track

Recessed | Straight circuit joint
A10-CDS




Recessed| Straight circuit joint 2m power cable
A20-CDS




UNIVERSAL ACCESSORIES


End cap
40-CDS




End cap 2m power cable
30-CDS



2 x Reinforced joint
50-CDS




Surface mounted
reinforced plate
60-CDS



SHADOWLINE
LED LINEAR TRACK SYSTEM

LED DOWNLIGHT MODULE FOR TRACK






H.55mm D.33mm


- Aluminium extrusion body
- ABS plastic baffle
- In 3 sizes - 5 LED, 10 LED or 15 LED version
- Driver required

Product code	Length	LED Consumption	Voltage	Lumen	Beam angle	Light temp.	CRI
A5047161	163mm	11W	48V DC	200 lm x 5	10° / 15° / 30°	3000°K	90+
B5047161	318mm	22W	48V DC	200 lm x 10	10° / 15° / 30°	3000°K	90+
C5047161	473mm	33W	48V DC	200 lm x 15	10° / 15° / 30°	3000°K	90+

SHADOWLINE
LED LINEAR TRACK SYSTEM

LINEAR LED MODULE FOR TRACK






H.55mm D.33mm


- Aluminium extrusion body
- ABS plastic cover
- In 3 sizes
- Driver required

Product code	Length	LED Consumption	Voltage	Lumen	Beam angle	Light temp.	CRI
A6047161	303mm	9.2W	48V DC	469 lm	110°	3000°K	80+
B6047161	603mm	18.4W	48V DC	938 lm	110°	3000°K	80+
C6047161	903mm	27.5W	48V DC	1407 lm	110°	3000°K	80+

SHADOWLINE
LED LINEAR TRACK SYSTEM

LED SPOT LIGHT MODULE FOR TRACK





Ø40mm D.33mm L.90mm


- Aluminium extrusion body
- PC plastic cover and lens
- Steel gear box
- Driver required

Product code	Length	LED Consumption	Voltage	Lumen	Beam angle	Light temp.	CRI
7047161	-	6.2W	48V DC	626 lm	10° / 20°	3000°K	90+

SHADOWLINE
LED LINEAR TRACK SYSTEM

LED TWIN HEAD DOWNLIGHT MODULE FOR TRACK





Ø33mm D.33mm L.105mm H.55mm

- Aluminium die-cast body
- ABS plastic baffle
- Diffuser version with 110° beam angle
- Lens version with 10° / 15° / 30° beam angle
- Driver required

Product code	Version	LED Consumption	Voltage	Lumen	Beam angle	Light temp.	CRI
9047161	Diffuser	5.3W	48V DC	124 lm x 2	110°	3000°K	80+
A9047161	Lens	4.4W	48V DC	200 lm x 2	10° / 15° / 30°	3000°K	90+



Diffuser
9047161




Lens
A9047161

SHADOWLINE
LED LINEAR TRACK SYSTEM

LED PENDANT MODULE FOR TRACK






Ø40mm H.250mm

- Aluminium extrusion body
- ABS plastic baffle and lens
- Steel gear box
- Driver required

Product code	Length	LED Consumption	Voltage	Lumen	Beam angle	Light temp.	CRI
0147161	-	6.2W	48V DC	626 lm	10° / 20°	3000°K	90+

DRIVERS





- When using 24VDC driver, maximum length and maximum wattage connection will be 50% of 48DVC version

Product code	Manufacturer	Description	Power	Voltage
10-PDS	Meanwell	HRP-100-48 constant voltage	100W	48V DC
20-PDS	Meanwell	HRP-200-48 constant voltage	200W	48V DC
30-PDS	Meanwell	HRP-300-48 constant voltage	300W	48V DC

SHADOWLINE
LED LINEAR TRACK SYSTEM

EASY INSTALLATION






- Simple plug and play LED installation
- Track cover can be trimmed or moved to fit the LED module, creating a seamless appearance


SHADOWLINE
LED LINEAR TRACK SYSTEM

DLD CONTRACT


CONNECTION OPTIONS




- Various connection options
- Compatible with 48V DC and 24V DC driver




1 Single power, single track




Use power end cap 30-CDS as power feed




2 Single power, multiple tracks



Use the joint 10-CDS to connect the tracks



3 Multiple power, multiple tracks




Don't install fixture between tracks when a new driver is connected to the circuit.

Use power joint 20-CDS to connect extra drivers


SHADOWLINE
LED LINEAR TRACK SYSTEM


INSTALLATION




- Continuous lengths of track can be joined, making it a truely flexible solution
- By segregating with multiple drivers separate lighting sections can be created, giving control over lighting different areas.

DRIVER INSTALLATION







01189 889414
enquiries@dld-contract.co.uk
dld-contract.co.uk

DLD Contract Ltd
Unit 9 Brookside Business Centre
Church Road
Swallowfield
Reading
Berkshire
RG7 1TH