## **WIREFLOW**



Reference

0374.

Application

Hanging lamps

**Installation type** 

Surface

## Description

Wireflow designed by Arik Levy. A hanging lamp which reviews and updates the chandelier look through an exercise of simplification that explores its essence and enhances its outline with great delicacy and at the same time a strong formal presence. Its appearance, as a structure of fine cables finished with 43 4.5W LED terminals, discretely connects with classic chandelier models, taking this type of lamp to a new, groundbreaking and futuristic dimension. Employing CREA product configurator software, the design can be modified to adapt to your specific project requirements.

Diffuser


Pressed-glass diffuser

Finish



Black lacquer

Sketch



**Electrical characteristics** 

43 x LED 4,5W 350mA



Total 192.6 W





**Physical characteristics** 

2 Box / 0.09 x 1.62 x 1.63 m. / Vol. 0.5035  $m^3\,/$ Gross weight 57.0 kg. / Net weight 47.0 kg.

Installation and assembly

Please, see the installation manual

**Light distribution** 

## **General lighting**

Lamp for general lighting that equally distributes the light in all directions.




Photometric data

Efficiency: 39.81% Isolux : Floor Coordinate system : CG Light position :

X=0.00m Y=0.00m Z=2.50m Total flux : 21082.00

Maximum value : 54.85 Light position: C=40.00 G=50.00 Symmetry on the planes : Double symmetrical



Certificates











