




BOULY 4 OUT



Material

PMMA

Materiaal

PMMA

Matériau

PMMA



Finish

PMMA : transparent
lens : PMMA

Afwerking

PMMA : transparent
lens : PMMA

Finition

PMMA : transparent
lentille : PMMA

Lightsource

4 x power LED (included) 1.2W
cold white : 6000K - 440lm - CRI >75
warm white : 2850K - 360lm - CRI >93
beam : 10° - 25° - 40°

Lichtbron

4 x power LED (inclusief) 1.2W
koud wit : 6000K - 440lm - CRI >75
warm wit : 2850K - 360lm - CRI >93
lichtbundel : 10° - 25° - 40°

Source lumineuse

4 x power LED (inclus) 1.2W
blanc froid : 6000K - 440lm - CRI >75
blanc chaud : 2850K - 360lm - CRI >93
rayon de lumière : 10° - 25° - 40°

Connection

350mA - driver excluded

Aansluiting

350mA - voeding exclusief

Connexion

350mA - convertisseur exclus

Specifications

outdoor
recessed
class III
IP65

Specificaties

buiten
inbouw
klasse III
IP65

Spécifications

extérieur
encastré
classe III
IP65

Optional

LED driver, 1-6W
to build in, not dimmable
23 x 66 x 35 mm

Optioneel

LED voeding, 1-6W
inbouw, niet dimbaar
23 x 66 x 35 mm

Option

LED convertisseur, 1-6W
encastré, non-dimmable
23 x 66 x 35 mm

