




BOULY C50 DOWN



Material

aluminium - PMMA

Materiaal

aluminium - PMMA

Matériau

aluminium - PMMA



Finish

black - chrome - gold - grey - ivory - white
PMMA : transparent
lens : PMMA

Afwerking

zwart - chroom - goud - grijs - ivoor - wit
PMMA : transparent
lens : PMMA

Finition

noir - chrome - or - gris - ivoire - blanc
PMMA : transparent
lentille : PMMA

Lightsource

4 x power LED (included) 1.2W
cold white : 6000K - 440lm - CRI >75
warm white : 2850K - 360lm - CRI >93
beam : 10° - 25° - 40°

Lichtbron

4 x power LED (inclusief) 1.2W
koud wit : 6000K - 440lm - CRI >75
warm wit : 2850K - 360lm - CRI >93
lichtbundel : 10° - 25° - 40°

Source lumineuse

4 x power LED (inclus) 1.2W
blanc froid : 6000K - 440lm - CRI >75
blanc chaud : 2850K - 360lm - CRI >93
rayon de lumière : 10° - 25° - 40°

Connection

350mA - driver excluded

Aansluiting

350mA - voeding exclusief

Connexion

350mA - convertisseur exclus

Specifications

indoor
ceiling mounting
class III
IP40

Specificaties

binnen
plafondmontage
klasse III
IP40

Spécifications

intérieur
plafonnier
classe III
IP40

Optional

LED driver max. 4 x 1.2W
to build in, not dimmable
42 x 40 x 22 mm

Optioneel

LED voeding max. 4 x 1.2W
inbouw, niet dimbaar
42 x 40 x 22 mm

Option

LED convertisseur max. 4 x 1.2W
encastré, non-dimmable
42 x 40 x 22 mm

