




BOULY WALL/CEILING



Material	Materiaal	Matériau
aluminium - PMMA	aluminium - PMMA	aluminium - PMMA
Finish	Afwerking	Finition
black - chrome - gold - grey - ivory - white PMMA : transparent lens : PMMA	zwart - chroom - goud - grijs - ivoor - wit PMMA : transparent lens : PMMA	noir - chrome - or - gris - ivoire - blanc PMMA : transparent lentille : PMMA
Lightsource	Lichtbron	Source lumineuse
4 x power LED (included) 1.2W cold white : 6000K - 440lm - CRI >75 warm white : 2850K - 360lm - CRI >93	4 x power LED (inclusief) 1.2W koud wit : 6000K - 440lm - CRI >75 warm wit : 2850K - 360lm - CRI >93	4 x power LED (inclus) 1.2W blanc froid : 6000K - 440lm - CRI >75 blanc chaud : 2850K - 360lm - CRI >93
Connection	Aansluiting	Connexion
350mA - driver excluded	350mA - voeding exclusief	350mA - convertisseur exclus
Specifications	Specificaties	Spécifications
indoor wall or ceiling mounting class III IP40	binnen wand- of plafondmontage klasse III IP40	intérieur applique ou plafonnier classe III IP40
Optional	Optioneel	Option
LED driver max. 4 x 1.2W to build in, not dimmable 42 x 40 x 22 mm	LED voeding max. 4 x 1.2W inbouw, niet dimbaar 42 x 40 x 22 mm	LED convertisseur max. 4 x 1.2W encastré, non-dimmable 42 x 40 x 22 mm

