




## BUCKY C50 DOWN



### Material

aluminium

### Materiaal

aluminium

### Matériau

aluminium



### Finish

black - chrome - gold - grey - ivory - white  
lens : PMMA

### Afwerking

zwart - chroom - goud - grijs - ivoor - wit  
lens : PMMA

### Finition

noir - chrome - or - gris - ivoire - blanc  
lentille : PMMA

### Lightsource

4 x power LED (included) 1.2W  
cold white : 6000K - 440lm - CRI >75  
warm white : 2850K - 360lm - CRI >93  
beam : 10° - 25° - 40°

### Lichtbron

4 x power LED (inclusief) 1.2W  
koud wit : 6000K - 440lm - CRI >75  
warm wit : 2850K - 360lm - CRI >93  
lichtbundel : 10° - 25° - 40°

### Source lumineuse

4 x power LED (inclus) 1.2W  
blanc froid : 6000K - 440lm - CRI >75  
blanc chaud : 2850K - 360lm - CRI >93  
rayon de lumière : 10° - 25° - 40°

### Connection

350mA - driver excluded

### Aansluiting

350mA - voeding exclusief

### Connexion

350mA - convertisseur exclus

### Specifications

indoor  
ceiling mounting  
class III  
IP40

### Specificaties

binnen  
plafondmontage  
klasse III  
IP40

### Spécifications

intérieur  
plafonnier  
classe III  
IP40

### Optional

LED driver max. 4 x 1.2W  
to build in, not dimmable  
42 x 40 x 22 mm

### Optioneel

LED voeding max. 4 x 1.2W  
inbouw, niet dimbaar  
42 x 40 x 22 mm

### Option

LED convertisseur max. 4 x 1.2W  
encastré, non-dimmable  
42 x 40 x 22 mm

