



## CRI-ATE 92 GT2-W/C

2 lighting sides

### Material

aluminium - PMMA

### Materiaal

aluminium - PMMA

### Matériau

aluminium - PMMA

### Finish

anodised aluminium - white  
PMMA : white (other colours on demand)

### Afwerking

geanodiseerd aluminium - wit  
PMMA : wit (andere kleuren op aanvraag)

### Finition

aluminium anodisé - blanc  
PMMA : blanc (autres couleurs sur demande)

### Lightsources

G5 - 2 x T5 21W/39W  
G53 - 2 x QR111 max. 50W

### Lichtbron

G5 - 2 x T5 21W/39W  
G53 - 2 x QR111 max. 50W

### Source lumineuse

G5 - 2 x T5 21W/39W  
G53 - 2 x QR111 max. 50W

### Connection

230V - gear included  
transformer included

### Aansluiting

230V - elektr. voorschakelapp. inclusief  
transformator inclusief

### Connexion

230V - ballast électr. inclus  
transformateur inclus

### Specifications

indoor  
wall or ceiling mounting  
class I  
IP20

### Specificaties

binnen  
wand- of plafondmontage  
klasse I  
IP20

### Spécifications

intérieur  
applique ou plafonnier  
classe I  
IP20