


ATLAS BAFFLE


LED IP44 ADJUSTABLE RECESSED DOWNLIGHT
DLD/7318161

DLD
CONTRACT



Dimensions

Ø76mm, H.87mm



Cutout

Ø68mm



- Removable light engine - simple twist mechanism
- IP44 - suitable for bathroom installation
- Adjustable by 20° tilt
- Complete with phase dimming driver
- Die-cast aluminium luminaire

- Forged aluminium heat sink
- Plastic PC reflector
- Bezel finish: white
- Baffle finish: black
- Optional honeycomb louvre, diffusion sheet or striped glass

ATLAS BAFFLE

LED IP44 ADJUSTABLE RECESSED DOWNLIGHT
DLD/7318161



TECHNICAL OVERVIEW

LED Consumption	13W		
Current	350mA		
CCT	2700K	3000K	4000K
Lumen ^{*1}	1336lm	1387lm	1411lm
Øsystem ^{*3}	-	-	-
Voltage	37.1V		
Reflector	15°/24°/38°/60° - Lens:10°		
CRI	90+		
Driver	Remoted, I/P: 90-264V 50/60HZ O/P: 12-48V 350mA 16W max.		
Insulation	Class II		
Protection	IP44		
Tilt	0~20°		
Rotation	-		
Operating Temperature	-20~40°		
Average Failure Time	L70(10k) >60000 (h)		

MATERIALS

Luminaire	Aluminium die-cast
Reflector	Plastic-PC
Heat Sink	Forged aluminium

*1. LUMEN : for LED chip test results based on Tc=85°C.

This is the ideal (maximum) lumen. This lumen information is from the LED supplier.

*3. LUMEN (Øsystem) (Total FLUX) : this lumen is from a luminaire with heat sink, reflector and fixture, this is the real lumen value including the loss due to different designs of reflectors and fixtures.

ATLAS BAFFLE

LED IP44 ADJUSTABLE RECESSED DOWNLIGHT
DLD/7318161

DLD
CONTRACT

LENS



Diffusion Sheet STD




Honeycomb Louvre HL



Striped Glass SG

FIRE RATED CANISTER



Fire rated canister (optional)



Version with baffle



Flush version without baffle

ATLAS BAFFLE

LED IP44 ADJUSTABLE RECESSED DOWNLIGHT
DLD/7318161


DLD
CONTRACT

PHOTOMETRIC DATA


LED: Citizen
Beam angle: 15°
Light colour temp.: 2700°K

Total flux: 555.17 lm
Efficiency: 42.1 %
Efficacy: 35.19 lm/W


LUMINOUS INTENSITY DISTRIBUTION DIAGRAM




ISOCANDELA DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



AAI FIGURE



ATLAS BAFFLE

LED IP44 ADJUSTABLE RECESSED DOWNLIGHT
DLD/7318161


DLD
CONTRACT

PHOTOMETRIC DATA


LED: Citizen
Beam angle: 24°
Light colour temp.: 2700°K

Total flux: 540.88 lm
Efficiency: 41.1 %
Efficacy: 34.29 lm/W


LUMINOUS INTENSITY DISTRIBUTION DIAGRAM




ISOCANDELA DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



AAI FIGURE



ATLAS BAFFLE

LED IP44 ADJUSTABLE RECESSED DOWNLIGHT
DLD/7318161


DLD
CONTRACT

PHOTOMETRIC DATA


LED: Citizen
Beam angle: 38°
Light colour temp.: 2700°K

Total flux: 536.74 lm
Efficiency: 40.7 %
Efficacy: 34.01 lm/W


LUMINOUS INTENSITY DISTRIBUTION DIAGRAM




ISOCANDELA DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



AAI FIGURE



ATLAS BAFFLE

LED IP44 ADJUSTABLE RECESSED DOWNLIGHT
DLD/7318161


DLD
CONTRACT

PHOTOMETRIC DATA


LED: Citizen
Beam angle: 60°
Light colour temp.: 2700°K

Total flux: 519.64 lm
Efficiency: 39.4 %
Efficacy: 32.88 lm/W


LUMINOUS INTENSITY DISTRIBUTION DIAGRAM




ISOCANDELA DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



AAI FIGURE



ATLAS BAFFLE

LED IP44 ADJUSTABLE RECESSED DOWNLIGHT
DLD/7318161

DLD
CONTRACT

PRODUCT CODE CONSTRUCTION

ATLAS BAFFLE LED IP44 ADJUSTABLE RECESSED DOWNLIGHT

DLD/7318161 / [X] / [X] / [X] / [X] / [X] / [X] / [X]

FIRE RATED:

[--]

[FRC]

None Fire rated canister

LENS:

[STD]

[HL]

[SG]

Standard diffusion sheet Honeycomb louvre Striped glass

LIGHT COLOUR TEMPERATURE (CCT):

[27K]

[30K]

2700°K

3000°K

BEAM ANGLE:

[15D]

[24D]

[38D]

[60D]

15°

24°

38°

60°

WATTAGE:

[13W]

12.9W

BAFFLE FINISH:

[BK]

Black

BEZEL FINISH:

[WH]

White



01189 889414



enquiries@dld-contract.co.uk



dld-contract.co.uk

DLD Contract Ltd
Unit 9 Brookside Business Centre
Church Road
Swallowfield
Reading
Berkshire
RG7 1TH