




## IZOR 28 G-H

1 or 2 lighting sides



### Material

aluminium - PMMA

### Materiaal

aluminium - PMMA

### Matériau

aluminium - PMMA



### Finish

anodised aluminium - white  
PMMA : white (other colours on demand)

### Afwerking

geanodiseerd aluminium - wit  
PMMA : wit (andere kleuren op aanvraag)

### Finition

aluminium anodisé - blanc  
PMMA : blanc (autres couleurs sur demande)

### Lightsource

2G11 - 2 x TC-L 24W

### Lichtbron

2G11 - 2 x TC-L 24W

### Source lumineuse

2G11 - 2 x TC-L 24W

### Connection

230V - gear included

### Aansluiting

230V - elektr. voorschakelapp. inclusief

### Connexion

230V - ballast électr. inclus

### Specifications

indoor  
suspension  
class I  
IP40

### Specificaties

binnen  
ophanging  
klasse I  
IP40

### Spécifications

intérieur  
suspension  
classe I  
IP40

### Optional

emergency model  
1 x 24W with battery  
battery : 3 x Ni-cd 3.6V + monitor LED

### Optioneel

emergency model  
1 x 24W met batterij  
batterij : 3 x Ni-cd 3.6V + LED monitor

### Option

emergency model  
1 x 24W avec batterie  
batterie : 3 x Ni-cd 3.6V + monitor LED