



IZOR 42 G-H

1 or 2 lighting sides

Material

aluminium - PMMA

Materiaal

aluminium - PMMA

Matériau

aluminium - PMMA



Finish

anodised aluminium - white
PMMA : white (other colours on demand)

Afwerking

geanodiseerd aluminium - wit
PMMA : wit (andere kleuren op aanvraag)

Finition

aluminium anodisé - blanc
PMMA : blanc (autres couleurs sur demande)

Lightsource

2G11 - 3 x TC-L 24W (dim. 4 x TC-L 24W)

Lichtbron

2G11 - 3 x TC-L 24W (dim. 4 x TC-L 24W)

Source lumineuse

2G11 - 3 x TC-L 24W (dim. 4 x TC-L 24W)

Connection

230V - gear included

Aansluiting

230V - elektr. voorschakelapp. inclusief

Connexion

230V - ballast électr. inclus

Specifications

indoor
suspension
class I
IP40

Specificaties

binnen
ophanging
klasse I
IP40

Spécifications

intérieur
suspension
classe I
IP40

Optional

emergency model
1 x 24W with battery
battery : 3 x Ni-cd 3.6V + monitor LED

Optioneel

emergency model
1 x 24W met batterij
batterij : 3 x Ni-cd 3.6V + LED monitor

Option

emergency model
1 x 24W avec batterie
batterie : 3 x Ni-cd 3.6V + monitor LED