

LINEAR TABLE FACT SHEET



LINEAR











Nominated 2015

With its VITACORE® touch panel, premium LED technology and ease of use, the entry level model stands at a compact 60 centimetre height and offers the same lighting benefits which make LUCTRA® the ideal lamp for the workplace.


TECHNICAL DATA

| | LINEAR | TABLE |
|---------------------------------------|---|------------------------|
| Product # | 9201 | |
| Colours | 01 black 02 white 23 aluminium | |
| Dimensions | Height: | 300 mm-750 mm |
| | Radius: | 100 mm-550 mm |
| | Lamp base: | 250 mm × 250 mm × 8 mm |
| Material | Aluminium, zinc, stee | I (lamp base), plastic |
| Weight | 6 kg | |
| Energy efficiency | A++* | |
| Protection type | IP 20 | |
| Protection class | Ⅲ◆ | |
| Illuminants | | |
| LEDs | 2 cold white & 2 warm white LEDs (CREE) | |
| Power consumption | 9,5 W** | |
| Luminous flux of luminaire: | neutral white 680 lm* | |
| Light intensity | neutral white 566 cd* | |
| Illuminance | 1,000 lux at a height of 60 cm | |
| Luminous efficiency | neutral white 73 lm/W* | |
| Colour temperature (CCT) | 2.700 K/3.600/6.500 K | |
| Colour reproduction index | ≥ 85 | |
| Operating temperature on lamp head | ≤ 40°C at 25°C ambient temperature | |
| Burning life | over 50,000 hours | |
| Standby consumption | ≤ 0,5 W | |
| Nominal voltage | 12-14 V DC | |
| Protection class | II 🖸 | |
| VITACORE® | | |
| Operation | via VITACORE® electronics | |
| Light strength setting | in 5 steps up to 1,000 lux | |
| Setting of light colour | in 3 steps 2,700 / 3,600 / 6,500 K | |
| Touch panel | made of acrylic glass | |
| D 1 3 | | |
| Power supply unit | | |
| Desktop power supply DC cable length | 1,5 m | |
| Nominal voltage | 1,5 III 100–240 V, 50–60 Hz | |
| | 1,5 A | |
| Power consumption Output | max. 12 V, 48 W, 4 A DC | |
| Output | max. 12 v, 48 W, 4 A DC | |

^{*}with warm white and cold white LEDs switched on **with cold white LEDs switched on to 100%

LINEAR TABLE 9201

LIGHT INTENSITY DISTRIBUTION



Free download on www.luctra.eu



DURABLE · Hunke & Jochheim GmbH & Co. KG

Westfalenstraße 77-79 · 58636 Iserlohn, Germany · Germany Postbox 1753 · 58634 Iserlohn, Germany Free service hotline 00800 00 582872 · Telephone +49 2371 662445 · info@luctra.de · www.luctra.eu

Free service Hotline