
# Mini Bollard Cat. No. BOLMINI



The Mini Bollard (95mm) is ideal for garden edges. The lens reflects light at two angles through an anti-glare mesh directly onto the ground and horizontally to illuminate the surrounding landscape.

Constructed of tubular aluminium with a UV stable powder coated finish or machined from solid copper or 316 stainless steel.



63.5mm



Ordering Information Luminaire Type Material/Finish Accessories - Black BOLMINI - Mini Bollard BK CJK150 - Cable Joint Kit ΒZ - Bronze HOOD140 - Anti Glare Hood GN - Green **LENSBOLF - Frosted Lens** STAR - Silver Star For an alternative LED WH - White option start at page 10.4 COP - Copper - 316 Stainless Steel SS Ordering Example: BOLMINI BK - Mini Bollard in Black HOOD140 BZ - Anti Glare Hood in Bronze (Accessories ordered separately)



HUNZA FACTORY 130 Felton Mathew Ave Glen Innes Auckland 1072 New Zealand

Ph: 64-9-528 9471 Fax: 64-9-528 9361 hunza@hunza.co.nz www.hunza.co.nz

# **INTERNATIONAL CONTACTS:** www.hunza.co.nz/contacts.php

Specifications may change without notice. Manufactured in New Zealand. © 2009 Hunza Holdings Ltd. Ver 1.4

## Luminaire Construction

CNC machined from one of the following metals:

High corrosion resistant 63.5mm  $(2\frac{1}{2})$  x 10mm (25/64) aluminium. End cap - solid aluminium 63.5mm  $(2\frac{1}{2})$  with chromate substrate and high UV resistant polyester powder coat.

**Colours** Black, Bronze, Green, Silver Star, White.

**Copper** 63.5mm (2½") x 10mm (13/32"). End cap - solid copper 63.5mm (2½").

**316 Stainless Steel** 63.5mm ( $2\frac{1}{2}$ ") x 9mm (11/32"). End cap - solid 316 stainless steel 63.5mm ( $2\frac{1}{2}$ ").

### Mounting

For mounting on top of posts, railings, etc. It is not suited for ground installation.

Features

#### Lens:

UV stable acrylic with anti-glare mesh projects light horizontally and at  $45^{\circ}$  onto the ground.

Gasket:

Silicone, iron impregnated 220°c (428°f).

Lamp Holders:

G4 -  $350^{\circ}$ c (662°f) ceramic multi contact lamp holder with  $250^{\circ}$ c (480°f) teflon cables.

### Accessories:

Cable Joint Kit (Cat. CJK150) Anti-Glare Hood - Not available in stainless steel (Cat. HOOD140). Frosted Lens (Cat. LENSBOLF) Standards

IP66 🕵 UL1838

Luminaire Weight

Alum .37kg (13oz) Cop .6kg (1lb 5oz) SS .5kg (1lb 1oz)

### Power Supply

HUNZA™ Inground or Wall Mount Transformer: not included.

USA and Canada:

HUNZA<sup>™</sup> Wall Mount Transformer: not included.

Luminaire: supplied with G4 20 watt lamp max. LED - Refer sheet no. 10.4 USA and Canada: G4 20 watt lamp max.

LED - Refer sheet no. 10.4



HUNZA FACTORY 130 Felton Mathew Ave Glen Innes Auckland 1072 New Zealand Ph: 64-9-528 9471 Fax: 64-9-528 9361 hunza@hunza.co.nz www.hunza.co.nz

# INTERNATIONAL CONTACTS: www.hunza.co.nz/contacts.php

Specifications may change without notice. Manufactured in New Zealand. © 2009 Hunza Holdings Ltd. Ver 1.4