




MINI-PI 1 IN



Material	Materiaal	Matériau
aluminium	aluminium	aluminium
Finish	Afwerking	Finition
black - grey - white lens : PMMA	zwart - grijs - wit lens : PMMA	noir - gris - blanc lentille : PMMA
Lightsource	Lichtbron	Source lumineuse
4 x power LED (included) 1.2W cold white : 6000K - 440lm - CRI >75 warm white : 2850K - 360lm - CRI >93 beam : 10° - 25° - 40°	4 x power LED (inclusief) 1.2W koud wit : 6000K - 440lm - CRI >75 warm wit : 2850K - 360lm - CRI >93 lichtbundel : 10° - 25° - 40°	4 x power LED (inclus) 1.2W blanc froid : 6000K - 440lm - CRI >75 blanc chaud : 2850K - 360lm - CRI >93 rayon de lumière : 10° - 25° - 40°
Connection	Aansluiting	Connexion
350mA - driver excluded	350mA - voeding exclusief	350mA - convertisseur exclus
Specifications	Specificaties	Spécifications
indoor recessed class III IP40 aperture : Ø 45 mm	binnen inbouw klasse III IP40 opening : Ø 45 mm	intérieur encastré classe III IP40 ouverture : Ø 45 mm
Optional	Optioneel	Option
LED driver max. 4 x 1.2W to build in, not dimmable 42 x 40 x 22 mm	LED voeding max. 4 x 1.2W inbouw, niet dimbaar 42 x 40 x 22 mm	LED convertisseur max. 4 x 1.2W encastré, non-dimmable 42 x 40 x 22 mm

