




MINI-PI 2 IN



Material

aluminium

Materiaal

aluminium

Matériau

aluminium



Finish

black - grey - white
lens : PMMA

Afwerking

zwart - grijs - wit
lens : PMMA

Finition

noir - gris - blanc
lentille : PMMA

Lightsource

8 x power LED (included) 1.2W
cold white : 6000K - 880lm - CRI >75
warm white : 2850K - 720lm - CRI >93
beam : 10° - 25° - 40°

Lichtbron

8 x power LED (inclusief) 1.2W
koud wit : 6000K - 880lm - CRI >75
warm wit : 2850K - 720lm - CRI >93
lichtbundel : 10° - 25° - 40°

Source lumineuse

8 x power LED (inclus) 1.2W
blanc froid : 6000K - 880lm - CRI >75
blanc chaud : 2850K - 720lm - CRI >93
rayon de lumière : 10° - 25° - 40°

Connection

350mA - driver excluded

Aansluiting

350mA - voeding exclusief

Connexion

350mA - convertisseur exclus

Specifications

indoor
recessed
class III
IP40
aperture : 2 x Ø 45 mm

Specificaties

binnen
inbouw
klasse III
IP40
opening : 2 x Ø 45 mm

Spécifications

intérieur
encastré
classe III
IP40
ouverture : 2 x Ø 45 mm

Optional

LED driver max. 8 x 1.2W
to build in, not dimmable
44 x 51 x 30 mm

Optioneel

LED voeding max. 8 x 1.2W
inbouw, niet dimbaar
44 x 51 x 30 mm

Option

LED convertisseur max. 8 x 1.2W
encastré, non-dimmable
44 x 51 x 30 mm

