



MINI-PI 2 UP

Material

aluminium

Materiaal

aluminium

Matériau

aluminium



Finish

black - grey - white
lens : PMMA

Afwerking

zwart - grijs - wit
lens : PMMA

Finition

noir - gris - blanc
lentille : PMMA

Lightsource

8 x power LED (included) 1.2W
cold white : 6000K - 880lm - CRI >75
warm white : 2850K - 720lm - CRI >93
beam : 10° - 25° - 40°

Lichtbron

8 x power LED (inclusief) 1.2W
koud wit : 6000K - 880lm - CRI >75
warm wit : 2850K - 720lm - CRI >93
lichtbundel : 10° - 25° - 40°

Source lumineuse

8 x power LED (inclus) 1.2W
blanc froid : 6000K - 880lm - CRI >75
blanc chaud : 2850K - 720lm - CRI >93
rayon de lumière : 10° - 25° - 40°

Connection

230V - driver included (not dimmable)

Aansluiting

230V - voeding inclusief (niet dimbaar)

Connexion

230V - convertisseur inclus (non-dimmable)

Specifications

indoor
ceiling mounting
class I
IP40

Specificaties

binnen
plafondmontage
klasse I
IP40

Spécifications

intérieur
plafonnier
classe I
IP40