

# Pillar Lite




Cat. No. PIL  
 Cat. No. PIL/R  
 Cat. No. PIL/GU



## UK & European Specification

The Pillar Lite illuminates both upwards and downwards, giving columns, gateway pillars and entrances a dramatic effect. The Retro™ is a 110/240-12 ac mains option suited to an installation where mounting a transformer is a problem, e.g. a brick wall where there is only the cable protruding out of the wall and it is not an option to recess the transformer or when replacing an existing light fitting. The base size increases in size to accommodate the encapsulated IP66 dimmable transformer.

This luminaire is machined from a choice of 10mm thick aluminium with a UV stable powder coated finish, solid copper or 316 stainless steel with a clear, tempered, flush glass lens and high temperature silicon gaskets.



## Ordering Information

Luminaire	Material/Finish	Accessories
PIL - Pillar Lite	BK - Black	CJK - Cable joint Kit
PIL/R - Retro	BZ - Bronze	LENSSTEPF - Frosted Lens
PIL/GU - GU10	GN - Green	GG - Glare Guard
	STAR - Silver Star	HCL - Hex Cell Louvre Adaptor
	WH - White	
	COP - Copper	
	SS - 316 Stainless	

Example: **PIL BK**

(Accessories ordered separately)

### Luminaire Construction

**CNC machined from one of the following metals:**

**Body:** High corrosion resistant low copper 63.5mm (2½") x 10mm (25/64") aluminium.

**Base & Mounting Plate:** Cast from virgin high corrosion resistant CC401 low copper aluminium alloy chromate substrate and high UV resistant polyester powder coat - Black, Bronze, Green, Silver Star, White.

**Body:** Copper 63.5mm (2½") x 10mm (25/64").

**Base:** Copper Hand spun 2mm (5/64").

**Mounting Plate:** Forged brass (Retro™).

**Body:** 316 Stainless steel 63.5mm (2½") x 9mm (11/32") rod.

**Base:** Investment cast and CNC machined (Retro™).

**Mounting Plate:** Investment cast and CNC machined.

### Mounting

12 volt: the luminaire is mounted to the wall using two 316 stainless screws through a shallow base 16mm (5/8") in depth.

Retro™ luminaire (110/240-12 volt): a mounting plate is fixed to the wall using two screws and then the luminaire is fixed to the mounting plate.

### Features

#### Lens:

10mm (3/8") clear flush fit shatter resistant glass.

Life Time Warranty.

#### Gaskets:

Silicone, iron impregnated 220°C (428°F)

#### Lamp Holders:

GU5.3 - 350°C (662°F) ceramic multi contact lamp holder with 250°C (480°F) teflon cables.

#### Accessories:

Cable Joint Kit (Cat. CJK150)

Frosted Lenses (Cat. LENSSTEPF).

Glare Guards (Cat. GG).

Hex Cell Louvre Adaptors (Cat. HCL).

Retro™ Transformer 110/240-12 volt (Cat. /R).

Wall Box Adaptor Plate.

### Standards

IP66 AS/NZS61046

UL1838

### Luminaire Weight

12 volt:

Alum .775kg (1lb 11oz)

SS 2.230kg (4lb 14oz)

BRZ 1.750kg (3lb 13oz)

Retro™:

Alum 1.100kg (2lb 6oz)

SS 2.650kg (5lb 13oz)

BRZ 2.200kg (4lb 13oz)

### Power Supply

12 volt

HUNZA™ Inground or HUNZA™ Wall Mount Transformer: not included.

RETRO™

HUNZA™ 110/240-12 volt ac silicone encapsulated electronic transformer built into the Retro™ base.

Dimmable with a suitable dimmer.

Approved for internal use.

### Supplied With

MR16 GU5.3 2 x 20 watt lamps max.

