




R54 RIMLESS LED



Material

aluminium

Materiaal

aluminium

Matériau

aluminium



Finish

interior : black - white
ring : black - grey - white
lens : PMMA

Afwerking

interieur : zwart - wit
ring : zwart - grijs - wit
lens : PMMA

Finition

intérieur : noir - blanc
anneau : noir - gris - white
lentille : PMMA

Lightsource

16 x power LED (included) 1.2W
cold white : 6000K - 1760lm - CRI >75
warm white : 2850K - 1440lm - CRI >93
beam : 10° - 25° - 40°

Lichtbron

16 x power LED (inclusief) 1.2W
koud wit : 6000K - 1760lm - CRI >75
warm wit : 2850K - 1440lm - CRI >93
lichtbundel : 10° - 25° - 40°

Source lumineuse

16 x power LED (inclus) 1.2W
blanc froid : 6000K - 1760lm - CRI >75
blanc chaud : 2850K - 1440lm - CRI >93
rayon de lumière : 10° - 25° - 40°

Connection

350mA - driver excluded

Aansluiting

350mA - voeding exclusief

Connexion

350mA - convertisseur exclus

Specifications

indoor
recessed
class III
IP40

Specificaties

binnen
inbouw
klasse III
IP40

Spécifications

intérieur
encastré
classe III
IP40

Accessories

installation kit : 370 x 145 x 82 mm
aperture : 325 x 90 x 84 mm

Accessoires

installatiekit : 370 x 145 x 82 mm
opening : 325 x 90 x 84 mm

Accessoires

kit d'installation : 370 x 145 x 82 mm
ouverture : 325 x 90 x 84 mm

