



SCAR-LED 1FD built-in 60

Material	Materiaal	Matériau
frame : aluminium flex : aluminium+metal - silicone lens : PMMA	frame : aluminium flex : aluminium+metaal - silicone lens : PMMA	structure : aluminium flex : aluminium+métal - silicone lentille : PMMA
Finish	Afwerking	Finition
polished varnished - black - white flex : polished varnished - white or black silicone	gepolijst en vernist - zwart - wit flex : gepolijst en vernist - witte of zwarte silicone	poli et vernis - blanc - noir flex : poli et vernis - silicone blanc ou noir
Lightsource	Lichtbron	Source lumineuse
1 x power LED (included) 1.2W cold white : 6000K - 110lm - CRI >75 warm white : 2850K - 90lm - CRI >93 beam : 10° - 25° - 40°	1 x power LED (inclusief) 1.2W koud wit : 6000K - 110lm - CRI >75 warm wit : 2850K - 90lm - CRI >93 lichtbundel : 10° - 25° - 40°	1 x power LED (inclus) 1.2W blanc froid : 6000K - 110lm - CRI >75 blanc chaud : 2850K - 90lm - CRI >93 rayon de lumière : 10° - 25° - 40°
Connection	Aansluiting	Connexion
230V - driver included (to build in, not dimmable)	230V - voeding inclusief (inbouw, niet dimbaar)	230V - convertisseur inclus (encastré, non-dimmable)
Specifications	Specificaties	Spécifications
indoor wall or ceiling mounting class I IP40	binnen wand- of plafondmontage klasse I IP40	intérieur applique ou plafonnier classe I IP40

