




SCAR-LED 1F built-in 45



Material

frame : aluminium
flex : aluminium+metaal - silicone
lens : PMMA

Materiaal

frame : aluminium
flex : aluminium+metaal - silicone
lens : PMMA

Matériau

structure : aluminium
flex : aluminium+métal - silicone
lentille : PMMA



Finish

polished varnished - black - white
flex : polished varnished - white or black silicone

Afwerking

gepolijst en vernist - zwart - wit
flex : gepolijst en vernist - witte of zwarte silicone

Finition

poli et vernis - blanc - noir
flex : poli et vernis - silicone blanc ou noir

Lightsource

1 x power LED (included) 1.2W
cold white : 6000K - 110lm - CRI >75
warm white : 2850K - 90lm - CRI >93
beam : 10° - 25° - 40°

Lichtbron

1 x power LED (inclusief) 1.2W
koud wit : 6000K - 110lm - CRI >75
warm wit : 2850K - 90lm - CRI >93
lichtbundel : 10° - 25° - 40°

Source lumineuse

1 x power LED (inclus) 1.2W
blanc froid : 6000K - 110lm - CRI >75
blanc chaud : 2850K - 90lm - CRI >93
rayon de lumière : 10° - 25° - 40°

Connection

350mA - driver excluded

Aansluiting

350mA - voeding exclusief

Connexion

350mA - convertisseur exclus

Specifications

indoor
wall or ceiling mounting
class III
IP40

Specificaties

binnen
wand- of plafondmontage
klasse III
IP40

Spécifications

intérieur
applique ou plafonnier
classe III
IP40

Optional

LED driver max. 4 x 1.2W
to build in, not dimmable

Optioneel

LED voeding max. 4 x 1.2W
inbouw, niet dimbaar

Option

LED convertisseur max. 4 x 1.2W
encastré, non-dimmable

