



SCAR-LED 2FDS

Material

frame : aluminium
flex : aluminium+metaal - silicone
lens : PMMA

Materiaal

frame : aluminium
flex : aluminium+metaal - silicone
lens : PMMA

Matériau

structure : aluminium
flex : aluminium+métal - silicone
lentille : PMMA



Finish

polished varnished - black - white
flex : polished varnished - white or black silicone

Afwerking

gepolijst en vernist - zwart - wit
flex : gepolijst en vernist - witte of zwarte silicone

Finition

poli et vernis - blanc - noir
flex : poli et vernis - silicone blanc ou noir

Lightsource

2 x power LED (included) 1.2W
cold white : 6000K - 220lm - CRI >75
warm white : 2850K - 180lm - CRI >93
beam : 10° - 25° - 40°

Lichtbron

2 x power LED (inclusief) 1.2W
koud wit : 6000K - 220lm - CRI >75
warm wit : 2850K - 180lm - CRI >93
lichtbundel : 10° - 25° - 40°

Source lumineuse

2 x power LED (inclus) 1.2W
blanc froid : 6000K - 220lm - CRI >75
blanc chaud : 2850K - 180lm - CRI >93
rayon de lumière : 10° - 25° - 40°

Connection

230V - driver included (not dimmable)

Aansluiting

230V - voeding inclusief (niet dimbaar)

Connexion

230V - convertisseur inclus (non-dimmable)

Specifications

indoor
wall or ceiling mounting
class I
IP40

Specificaties

binnen
wand- of plafondmontage
klasse I
IP40

Spécifications

intérieur
applique ou plafonnier
classe I
IP40