




ZEZE OUT

1 lighting side



Material

aluminium - glass

Materiaal

aluminium - glas

Matériau

aluminium - verre

Finish

anodised aluminium - white
glass frame : anodised aluminium
glass : frosted

Afwerking

geanodiseerd aluminium - wit
glas frame : geanodiseerd aluminium
glas : mat

Finition

aluminium anodisé - blanc
structure de verre : aluminium anodisé
verre : sablé

Lightsource

GY6.35 - 1 x QT12 max. 50W

Lichtbron

GY6.35 - 1 x QT12 max. 50W

Source lumineuse

GY6.35 - 1 x QT12 max. 50W

Connection

12V - transformer excluded

Aansluiting

12V - transformator exclusief

Connexion

12V - transformateur exclus

Specifications

outdoor
wall mounting
class III
IP55

Specificaties

buiten
wandmontage
klasse III
IP55

Spécifications

extérieur
applique
classe III
IP55

Accessories



cover plate : Ø80 mm
anodised aluminium

Accessoires

afdekplaat : Ø80 mm
geanodiseerd aluminium

Accessoires

cache : Ø80 mm
aluminium anodisé



cover plate : 100 x 100 mm
anodised aluminium - white

afdekplaat : 100 x 100 mm
geanodiseerd aluminium - wit

cache : 100 x 100 mm
aluminium anodisé - blanc