

Utförande: Naturanodiserad aluminium, natur, mörkgrå- eller bronslackerad.

Bländskydd av prismatic akryl.

LED information: Systemeffekt 17W.alt 26W Armaturlumen 1400LM

alt 1937LM. Korrelerad färgtemperatur 3000K. Färgtolerans SDCM 3.

Färgåtergivning RA 80.

Montage: I tak, pendlad i 1,7m vajer.

Anslutning: Kopplingsplint 5x4mm². Överkopplingsbar.

Design: Per Sundstedt.

W	FÄRG/FINISH	ART
LED 1400LM	Alu/Alu	7428-3-38
LED 1400LM	Alu/Alu	7428-3-38HFF
LED 1400LM	Brons/Bronze	7428-3-97
LED 1400LM	Brons/Bronze	7428-3-97HFF
LED 1400LM	Grå/Grey	7428-3-97
LED 1400LM	Grå/Grey	7428-3-97HFF
LED 1937LM	Alu/Alu	7430-3-38
LED 1937LM	Alu/Alu	7430-3-38HFF
LED 1937LM	Brons/Bronze	7430-3-97
LED 1937LM	Brons/Bronze	7430-3-97HFF
LED 1937LM	Grå/Grey	7430-3-98
LED 1937LM	Grå/Grey	7430-3-98HFF

HFF = Dimmbar med DALI, DSI, SwitchDim

HFF = Dimmable with DALI, DSI, SwitchDim

Finish: Anodized aluminium, natural, bronze or dark grey painted and white

painted steel. Diffuser in prismatic acrylic.

LED information: System power: 17W. or 26W. Luminaire Luminous Flux:

1400LM or 1937LM. CCT 3000K. SDCM 3. CRI 80.

Installation: Ceiling-installation, 1,7 m wire.

Connection: Terminal-block 5x4mm². Two entry holes.

Design: Per Sundstedt.

