



**Utförande:** Naturanodiserad aluminium, natur, mörkgrå- eller bronslackerad. Bländskydd av prismatic akryl.

**LED info:** Systemeffekt 13W. Armaturlumen 816LM. Korrelerad färgtemperatur 3000K. Färgtolerans SDCM 3. Färgåtergivning RA 80.

**Montage:** Dikt tak.

**Anslutning:** Snabbkopplingsplint 3x4mm<sup>2</sup> . vid HFF 5x5mm<sup>2</sup>, överkopplingsbar.

**Design:** Per Sundstedt.

W	FÄRG/FINISH	ART
LED 816LM	Aluminium/Aluminum	7407-1-38
LED 816LM	Aluminium/Aluminum	7407-1-38HFF
LED 816LM	Brons/Bronze	7407-1-97
LED 816LM	Brons/Bronze	7407-1-97HFF
LED 816LM	Mörkgrå/Dark grey	7407-1-98
LED 816LM	Mörkgrå/Dark grey	7407-1-98HFF

HFF = Dimmbar - DALI, DSI, SwitchDim.  
HFF = Dimmable with DALI, DSI, SwitchDim

**Finish:** Anodized aluminium, natural, bronze or dark grey painted and white painted steel. Diffuser in prismatic acrylic.

**LED info:** System power: 13W. Luminaire Luminous Flux: 816LM. CCT 3000K. SDCM 3. CRI 80.

**Installation:** Ceiling-installation.

**Connection:** Terminal block. D108 mm 3x4mm<sup>2</sup> . D400 mm 5x4mm<sup>2</sup>, two entry holes.

**Design:** Per Sundstedt.

