



**Utförande:** Naturanodiserad aluminium, natur, mörkgrå- eller bronslackerad. Bländskydd av prismatic akryl.

**LED info:** Systemeffekt 17W alt 26W. Armaturlumen 1400LM alt 1937LMLM. Korrelerad färgtemperatur 3000K. Färgtolerans SDCM 3. Färgåtergivning RA 80.

**Montage:** Dikt tak.

**Anslutning:** Snabbkopplingsplint, D108 mm 3x4mm<sup>2</sup> . D400 mm 5x4mm<sup>2</sup>, överkopplingsbar.

**Design:** Per Sundstedt.

| W           | D/MM | KG  | ART          |
|-------------|------|-----|--------------|
| 1x40W/2Gx13 | 400  | 3,4 | 7408-3-XX    |
| 1x40W/2Gx13 | 400  | 3,4 | 7408-3-XXHFF |
| 1x55W/2Gx13 | 400  | 3,4 | 7409-3-XX    |
| 1x55W/2Gx13 | 400  | 3,4 | 7409-3-XXHFF |
| LED 1400LM  | 400  | 3,3 | 7407-3-XX    |
| LED 1400LM  | 400  | 3,3 | 7407-3-XXHFF |
| LED 1937LM  | 400  | 3,3 | 7429-3-XX    |
| LED 1937LM  | 400  | 3,3 | 7429-3-XXHFF |

**Med inbyggd närvarosensor/With built in motion detector**

|            |     |     |               |
|------------|-----|-----|---------------|
| LED/1400LM | 400 | 3,3 | 7407-3-XXS    |
| LED/1400LM | 400 | 3,3 | 7407-3-XXHFFS |
| LED 1937LM | 400 | 3,3 | 7429-3-XXS    |
| LED 1937LM | 400 | 3,3 | 7429-3-XXHFFS |

**Med nödljus 1h/With emergency light 1h**

|            |     |     |               |
|------------|-----|-----|---------------|
| LED/1400LM | 400 | 3,3 | 7407-3-XXE    |
| LED/1400LM | 400 | 3,3 | 7407-3-XXHFFE |
| LED 1937LM | 400 | 3,3 | 7429-3-XXE    |
| LED 1937LM | 400 | 3,3 | 7429-3-XXHFFE |

XX = Färg/Color -38 Aluminium, -97 Brons/Bronze, -98 Mörkgrå/Dark grey.

HFF = Dimmbar - DALI, DSI, SwitchDim.

HFF = Dimmable with DALI, DSI, SwitchDim

**TILLBEHÖR/ACCESSORIES**

Närvarosensor till 7408/7409/Motion detector to 7408/7409 **98900-1-01**

**Finish:** Anodized aluminium, natural, bronze or dark grey painted and white painted steel. Diffuser in prismatic acrylic.

**LED info:** System power: 17W or 26W. Luminaire Luminous Flux: 1400LM or 1937LM. CCT 3000K. SDCM 3. CRI 80.

**Installation:** Ceiling-installation.

**Connection:** Terminal block. D108 mm 3x4mm<sup>2</sup> . D400 mm 5x4mm<sup>2</sup>, two entry holes.

**Design:** Per Sundstedt.

