

Takarmatur som är perfekt vid lägre takhöjder, då den endast bygger 100 mm ner från tak.

Utförande: Mörkgrå strukturlack. Skärm av matt opalglas.

Montage: Dikt tak.

Anslutning: Snabbkopplingsplint 5x4mm². Överkopplingsbar. Distans för utanpåliggande kabel finns som tillbehör.

Design: Per Sundstedt.

LED info: Systemeffekt 17W. Armaturlumen 1290LM. Korrelerad färgtemperatur 3000K. Färgtolerans SDCM 3. Färgåtergivning RA 80.

W	SKÄRM/SHADE	KG	ART
1x22W/2Gx13	Glas/Glass	2,3	4065-1-21HF
1x22W/2Gx13	Glas/Glass	2,3	4065-1-21HFF
LED 1290LM	Glas/Glass	2,5	4066-1-21
LED 1290LM	Glas/Glass	2,5	4066-1-21HFF

Med inbyggd närvarosensor/With built-in motion detector

LED 1290LM	Glas/Glass	2,5	4066-1-21S
LED 1290LM	Glas/Glass	2,5	4066-1-21HFFS

HFF = Dimmbar - DALI, DSI, SwitchDim.

HFFS = Dimmable with DALI, DSI, SwitchDim

TILLBEHÖR/ACCESSORY

Distans för utanpåliggande ledning	94063-1-01
<i>Distance-piece for external mains cable</i>	
Närvarosensor till 4065/Motion detector for 4065	98900-1-01

Finish: Dark-grey painted steel. Shade in matt opal glass.

Installation: Ceiling-installation.

Connection: Snap-in terminal block 5x4mm². Two cable entries. Distance-piece for external mains cable available as accessory.

Design: Per Sundstedt.

LED info: System power: 17W. Luminaire Luminous Flux: 1290LM. CCT 3000K. SDCM 3. CRI 80.

