

Utförande: Stomme i vitlackerad metall. Bländskydd av matt akryl.

Gummitrådar i olika färger. Det går även att mixa två färger på begäran.

LED info: Systemeffekt 17W. Armaturlumen 1260LM. Korrelerad färgtemperatur 3000K. Färgtolerans SDCM 3. Färgåtergivning RA 80.

Montage: Dikt tak.

Anslutning: Snabbkopplingsplint 5x4mm².

Design: Mia Cullin 2012.

| W | D | FÄRG/FINISH | ART. |
|------------|-----|-------------|--------------|
| 40W/2Gx13 | 413 | Vit/White | 8212-1-XX |
| 40W/2Gx13 | 413 | Vit/White | 8212-1-XXHFF |
| 55W/2Gx13 | 413 | Vit/White | 8213-1-XX |
| 55W/2Gx13 | 413 | Vit/White | 8213-1-XXHFF |
| LED/1260LM | 413 | Vit/White | 8214-1-XX |
| LED/1260LM | 413 | Vit/White | 8214-1-XXHFF |

Med inbyggd närvarosensor/With built-in motion detector

| | | | |
|------------|-----|-----------|---------------|
| LED/1260LM | 413 | Vit/White | 8214-1-XXS |
| LED/1260LM | 413 | Vit/White | 8214-1-XXHFFS |

Med inbyggd nödljus enhet/With built-in emergency pack

| | | | |
|------------|-----|-----------|---------------|
| LED/1260LM | 413 | Vit/White | 8214-1-XXE |
| LED/1260LM | 413 | Vit/White | 8214-1-XXHFFE |

XX = Gummiband -01 vit, -06 svart, -12 grön, -14 gul, -41 orange.

XX = Rubberband -01 white, -06 black, -12 green, -14 yellow, -41 orange

HFF = Dimmbar - DALI, DSI, SwitchDim.

HFF = Dimmable with DALI, DSI, SwitchDim

TILLBEHÖR/ACCESSORIES

Närvarosensor till 8212, 8213/Motion detector to 8212, 8213 **98900-1-01**


Finish: Base in white painted metal. Diffuser in matt acrylic. Rubber bands in different colors. Possible to mix two colors on request.

LED info: System power: 17W. Luminaire Luminous Flux: 1260LM. CCT 3000K. SDCM 3. CRI 80.

Installation: Ceiling.

Connection: Terminal block 5x4mm².

Design: Mia Cullin 2012.



Utförande: Stomme i vitlackerad metall. Bländskydd av matt akryl.
Gummitrådar i olika färger. Det går även att mixa två färger på begäran.
LED info: Systemeffekt 17W. Armaturlumen 1323LM. Korrelerad färgtemperatur 3000K. Färgtolerans SDCM 3. Färgåtergivning RA 80.
Montage: Dikt tak.
Anslutning: Snabbkopplingsplint 5x4mm².
Design: Mia Cullin 2012.

| W | D | FÄRG/FINISH | ART. |
|------------|-----|-------------|--------------|
| 40W/2Gx13 | 600 | Vit/White | 8212-3-XX |
| 40W/2Gx13 | 600 | Vit/White | 8212-3-XXHFF |
| 55W/2Gx13 | 600 | Vit/White | 8213-3-XX |
| 55W/2Gx13 | 600 | Vit/White | 8213-3-XXHFF |
| LED/1323LM | 600 | Vit/White | 8214-3-XX |
| LED/1323LM | 600 | Vit/White | 8214-3-XXHFF |

Med inbyggd närvarosensor/With built-in motion detector

| | | | |
|------------|-----|-----------|---------------|
| LED/1323LM | 600 | Vit/White | 8214-3-XXS |
| LED/1323LM | 600 | Vit/White | 8214-3-XXHFFS |

Med inbyggd nödljus enhet/With built-in emergency pack

| | | | |
|------------|-----|-----------|---------------|
| LED/1323LM | 600 | Vit/White | 8214-3-XXE |
| LED/1323LM | 600 | Vit/White | 8214-3-XXHFFE |

XX = Gummitband -01 vit, -06 svart, -12 grön, -14 gul, -41 orange.

XX = Rubberband -01 white, -06 black, -12 green, -14 yellow, -41 orange

HFF = Dimmbar - DALI, DSI, SwitchDim.

HFF = Dimmable with DALI, DSI, SwitchDim

TILLBEHÖR/ACCESSORIES

Närvarosensor till 8212, 8213/Motion detector to 8212, 8213 **98900-1-01**

Finish: Base in white painted metal. Diffuser in matt acrylic. Rubber bands in different colors. Possible to mix two colors on request.

LED info: System power: 17W. Luminaire Luminous Flux: 1323LM. CCT 3000K. SDCM 3. CRI 80.

Installation: Ceiling.

Connection: Terminal block 5x4mm².

Design: Mia Cullin 2012.

