

Utförande: Perforerad metall med kvadratiska hål alt. sträckmetall.

Lackerad gul Ral 1018, orange Ral 2004, klarlackerad metall alt. transparent guldlack. Grid har ett rått uttryck och man kan se svetsfogar mm genom den transparenta lacken. Reflektor finns som tillbehör.

LED info: Systemeffekt se nedan. Armaturlumen se nedan. Korrelerad färgtemperatur 3000K. Färgtolerans SDCM 3. Färgåtergivning RA 80.

Montage: Dikt tak.

Anslutning: Snabbkopplingsplint 5x4mm².

Design: Front 2012.

W	MODELL/MODEL	ART.
T5 Lysrör/T5 Light tube		
T5 Eco 25/50W	Fyrkantshål/Square holes	8136-1-XX
T5 Eco 25/50W	Fyrkantshål/Square holes	8136-1-XXHFF
T5 Eco 25/50W	Sträckmetall/Expanded metal	8137-1-XX
T5 Eco 25/50W	Sträckmetall/Expanded metal	8137-1-XXHFF
LED/LED		
LED 1414LM/19W	Fyrkantshål/Square holes	8141-1-XX
LED 1414LM/19W	Fyrkantshål/Square holes	8141-1-XXHFF
LED 1414LM/19W	Sträckmetall/Expanded metal	8142-1-XX
LED 1414LM/19W	Sträckmetall/Expanded metal	8142-1-XXHFF
LED 2210LM/33W	Fyrkantshål/Square holes	8138-1-XX
LED 2210LM/33W	Fyrkantshål/Square holes	8138-1-XXHFF
LED 2210LM/33W	Sträckmetall/Expanded metal	8139-1-XX
LED 2210LM/33W	Sträckmetall/Expanded metal	8139-1-XXHFF
XX = -14 Gul/Yellow, -41 Orange/Orange, -76 Metall/Metal, -77 Guld/Gold		
HFF = Dimmbar - DALI, DSI, SwitchDim.		
HFF = Dimmable with DALI, DSI, SwitchDim		
TILLBEHÖR/ACCESSORY		
Reflektor T5/ Reflector T5		98130-1-82
Reflektor LED/ Reflector LED		98126-1-82

Finish: Perforated metal with square holes or expanded metal. Yellow Ral 1018, orange Ral 2004, clear painted metal or transparent gold varnish. Grid has a raw finish and one can see weldings through the transparent varnish. Reflector available as accessory.

LED info: System power: see above. Luminaire Luminous Flux: see above. CCT 3000K. SDCM 3. CRI 80.

Installation: Ceiling.

Connection: Terminal block 5x4mm².

Design: Front 2012.

