


Technical Data Sheet

Last data update

7/16/2016

9010
novantadieci®




Req. space behind the plasterboard

50mm




hole on the plasterboard

200x140mm



External measures

195x135mm




Measures of the light output

105x40mm



Height without electrical part

40mm



Height including the electrical part

40mm

Notes on measures

General notes

PASSO

4155B-4004

Recessed Spotlight / CRISTALY

Surface finish : CRISTALY

LED 2.2W / 24Vdc / 213lm / 4000°K / CRI85

Model

Code	4155B
Product family	PASSO
Type	Recessed Spotlight

Material/Surface finish

Code	004
Material	CRISTALY
Surface finish	CRISTALY

Electrical part

Code	4004
Type	LED
Power	2.2W
Tension	24Vdc
Light Output	213lm
Colour Temperature	4000°K
CRI	85
Light Output of the lamp	176,79lm
Dimmable	SI
Power Supply	by Remote Power Supply
Connection	2 PVC cables
Cover	Transparent Polycarbonate

General Data

Protection Index	IP20
Isolation Class	III
Weight [Kg]	0,95
Country of production	MADE IN ITALY
Mounting instruction	025.553_9010_REV02

Installation

Multisize system	SI
Position	Wall/Ceiling lighting


Packaging

Type	White american Box
Measures AxBxH	260x150x110mm
Gross Weight [Kg]	1,0379
Master carton	NO
Quantity of articles	
Measures AxBxH	

Technical Data Sheet

4155B-4004

Fotometric Data




<i>Electrical part</i>	4004_2,2
<i>Power</i>	2.2W
<i>Light Output</i>	213lm
<i>Colour Temperature</i>	4000°K
<i>CRI</i>	85
<i>Lamp Light Output</i>	83%
<i>Light Output of the lamp</i>	176,79lm
<i>Beam Angle</i>	63°
<i>Beam Inclination</i>	50°

<i>Illuminance</i>	0.3m	911lux
	0.5m	328lux
	1m	82lux


Accessories

Housing Box for Brickwork




<i>Code</i>	023.452
<i>Measures</i>	140X200X55mm
<i>Measures of the hole on</i>	170X230X65mm

Standard Power Supply



<i>Code</i>	026.258
<i>Measures</i>	130x42x23mm
<i>Power</i>	12W
<i>Input</i>	220-240V~W
<i>Output</i>	24Vdc




<i>Code</i>	026.259
<i>Measures</i>	167x45x30mm
<i>Power</i>	36W
<i>Input</i>	220-240V~W
<i>Output</i>	24Vdc




<i>Code</i>	026.260
<i>Measures</i>	157x54x36mm
<i>Power</i>	60W
<i>Input</i>	220-240V~W
<i>Output</i>	24Vdc

Dimmable Power Supply



<i>Code</i>	026.219
<i>Measures</i>	155x51x26mm
<i>Power</i>	21,6W
<i>Input</i>	220-240V~W
<i>Output</i>	24Vdc
<i>Dimmable</i>	PUSH/0-10V/DALI



<i>Code</i>	026.209
<i>Measures</i>	125x82x29mm
<i>Power</i>	60W
<i>Input</i>	220-240 V~W
<i>Output</i>	24Vdc
<i>Dimmable</i>	PUSH/1-10V

Technical Data Sheet

4155B-4004

9010
novantadieci®

Accessories

Other Accessories



<i>Code</i>	099.142
<i>Description</i>	Emergency Kit
<i>Notes</i>	