

**General notes**

**INCASSO A PLAFONE**

8935C-2715

Recessed Spotlight / CRISTALY  
 Surface finish : CRISTALY  
 LED 88W / 2x1050mA / 9880lm / 2700°K / CRI85

**Model**

Code	8935C
Product family	INCASSO A PLAFONE
Type	Recessed Spotlight

**Material/Surface finish**

Code	004
Material	CRISTALY
Surface finish	CRISTALY

**Electrical part**

Code	2715
Type	LED
Power	88W
Current	2x1050mA
Light Output	9880lm
Colour Temperature	2700°K
CRI	85
Light Output of the lamp	6916lm
Dimmable	SI
Power Supply	Power Supply in counterceiling
Connection	2 PVC cables
Cover	Etched Glass

**General Data**

Protection Index	IP20-IP44
Isolation Class	III
Weight [Kg]	28,5
Country of production	MADE IN ITALY
Mounting instruction	025.504_9010_REV03

**Installation**

Multisize system	NO
Position	Ceiling


**Packaging**

Type	SCATOLA AMERICANA AVANA
Measures AxBxH	1210x1210x460mm
Gross Weight [Kg]	42,306
Master carton	NO
Quantity of articles	
Measures AxBxH	

# Technical Data Sheet

8935C-2715

## Fotometric Data



<i>Electrical part</i>	2715
<i>Power</i>	88W
<i>Light Output</i>	9880lm
<i>Colour Temperature</i>	2700°K
<i>CRI</i>	85
<i>Lamp Light Output</i>	70%
<i>Light Output of the lamp</i>	6916lm
<i>Beam Angle</i>	106°
<i>Beam Inclination</i>	0°

<i>Illuminance</i>	1m	2580lux
	2m	645lux
	3m	287lux
	4m	161lux
	5m	103lux

## Accessories

### Standard Power Supply


<i>Code</i>	2x026.205
<i>Measures</i>	128x60x31,5mm
<i>Power</i>	min35,7W max59,9W
<i>Input</i>	180-295V~W
<i>Output</i>	1050mA

### Dimmable Power Supply

<i>Code</i>	2x026.206.3
<i>Measures</i>	124x82x23mm
<i>Power</i>	59,9W
<i>Input</i>	180-295V~W
<i>Output</i>	1050mA
<i>Dimmable</i>	PUSH/DALI

<i>Code</i>	2x026.207.3
<i>Measures</i>	124x82x23mm
<i>Power</i>	59,9W
<i>Input</i>	180-295V~W
<i>Output</i>	1050mA
<i>Dimmable</i>	0-10V

## Other Accessories



<i>Code</i>	099.142
<i>Description</i>	Emergency Kit
<i>Notes</i>	