


Req. space behind the plasterboard

30mm




hole on the plasterboard

410x410mm



External measures

405x405mm




Measures of the light output

Ø111mm



Height without electrical part

25mm



Protrusion

260mm



General notes

INCASSO A PLAFONE

8935D-4008

Recessed Spotlight / CRISTALY

Surface finish : CRISTALY

LED 13W / 700mA / 1700lm / 4000°K / CRI85

Model

Code	8935D
Product family	INCASSO A PLAFONE
Type	Recessed Spotlight

Material/Surface finish

Code	004
Material	CRISTALY
Surface finish	CRISTALY

Electrical part

Code	4008
Type	LED
Power	13W
Current	700mA
Light Output	1700lm
Colour Temperature	4000°K
CRI	85

Light Output of the lamp	1479lm
Dimmable	SI

Power Supply	Power Supply in counterceiling
Connection	2 PVC cables
Cover	Satin Polycarbonate

General Data

Protection Index	IP20
Isolation Class	III
Weight [Kg]	7,5
Country of production	MADE IN ITALY
Mounting instruction	025.450_9010_REV04

Installation

Multisize system	SI
Position	Ceiling

Packaging


Type	White american Box
Measures AxBxH	510x510x460mm
Gross Weight [Kg]	9,9527

Master carton	NO
Quantity of articles	
Measures AxBxH	

Technical Data Sheet

8935D-4008

Fotometric Data




<i>Electrical part</i>	4008
<i>Power</i>	13W
<i>Light Output</i>	1700lm
<i>Colour Temperature</i>	4000°K
<i>CRI</i>	85

<i>Illuminance</i>	1m	1557lux
	2m	389lux
	3m	173lux
	4m	97lux
	5m	62lux


<i>Lamp Light Output</i>	87%
<i>Light Output of the lamp</i>	1479lm
<i>Beam Angle</i>	52°
<i>Beam Inclination</i>	0°

Accessories

Standard Power Supply



<i>Code</i>	026.255
<i>Measures</i>	88,5x41x23mm
<i>Power</i>	min11,9W max18,2W
<i>Input</i>	220-240V~W
<i>Output</i>	700mA




<i>Code</i>	026.256
<i>Measures</i>	118x42,5x24mm
<i>Power</i>	min25,2W max35,7W
<i>Input</i>	220-240V~W
<i>Output</i>	700mA


Dimmable Power Supply



<i>Code</i>	026.219
<i>Measures</i>	155x51x26mm
<i>Power</i>	19,6W
<i>Input</i>	220-240V~W
<i>Output</i>	700mA
<i>Dimmable</i>	PUSH/0-10V/DALI



<i>Code</i>	026.206
<i>Measures</i>	124x82x23mm
<i>Power</i>	60,2W
<i>Input</i>	180-295V~W
<i>Output</i>	700mA
<i>Dimmable</i>	PUSH/DALI



<i>Code</i>	026.207
<i>Measures</i>	124x82x23mm
<i>Power</i>	60,2W
<i>Input</i>	180-295V~W
<i>Output</i>	700mA
<i>Dimmable</i>	0-10V

LED bulbs

<i>Code</i>	L005-3020
<i>Power</i>	15W
<i>Tension</i>	220-240V
<i>Flux</i>	1200lm
<i>CRI</i>	85
<i>Colour Temperature</i>	3000°K
<i>Beam Angle</i>	60°

<i>Code</i>	L006-3022
<i>Power</i>	15W
<i>Tension</i>	220-240V
<i>Flux</i>	1200lm
<i>CRI</i>	85
<i>Colour Temperature</i>	3000°K
<i>Beam Angle</i>	30°

Technical Data Sheet

8935D-4008

9010
novantadieci®

Accessories

Other Accessories



<i>Code</i>	099.142
<i>Description</i>	Emergency Kit
<i>Notes</i>	