

Technical Data Sheet

Last data update


3/15/2016

9010
novantadieci®



Req. space behind the plasterboard

105mm



hole on the plasterboard

615x360mm




External measures

610x355mm




Measures of the light output

515x200mm



Height without electrical part

100mm



Height including the electrical part

100mm

Notes on measures

General notes

SONORE

M002B-2734

Sonore recessed wall lamp / CRISTALY

Surface finish : CRISTALY

LED 32W / 1050mA / 4600lm / 2700°K / CRI85

Model

| | |
|----------------|---------------------------|
| Code | M002B |
| Product family | SONORE |
| Type | Sonore recessed wall lamp |

Material/Surface finish

| | |
|----------------|----------|
| Code | 004 |
| Material | CRISTALY |
| Surface finish | CRISTALY |

Electrical part

| | |
|--------------------|--------|
| Code | 2734 |
| Type | LED |
| Power | 32W |
| Current | 1050mA |
| Light Output | 4600lm |
| Colour Temperature | 2700°K |
| CRI | 85 |

Dati sistema Sonore

| | |
|-----------------------|--------------------|
| N° Driver | 2 |
| Impedenza | 8 Ohm |
| Potenza nominale | 40 Wrms |
| Potenza di picco | 80 Wmax |
| Sensibilità | 85 dB/oct |
| Risposta in Frequenza | 200-20000 Hz |
| Input | da centralina M900 |

General Data

| | |
|-----------------------|--------------------|
| Protection Index | IP20 |
| Isolation Class | III |
| Cover | |
| Weight [Kg] | 7,5 |
| Country of production | MADE IN ITALY |
| Mounting instruction | 025.534_9010_REV01 |

Installation

| | |
|------------------|------|
| Multisize system | SI |
| Position | Wall |

Packaging


| | |
|-------------------|--------------------|
| Type | White american Box |
| Measures AxBxH | 690x440x165mm |
| Gross Weight [Kg] | 8,5269 |

| | |
|----------------------|----|
| Master carton | NO |
| Quantity of articles | |
| Measures AxBxH | |

Technical Data Sheet

M002B-2734

Fotometric Data




| | |
|---------------------------------|--------|
| <i>Electrical part</i> | 2734 |
| <i>Power</i> | 32W |
| <i>Light Output</i> | 4600lm |
| <i>Colour Temperature</i> | 2700°K |
| <i>CRI</i> | 85 |
| <i>Lamp Light Output</i> | 52% |
| <i>Light Output of the lamp</i> | 2392lm |
| <i>Beam Angle</i> | 70° |
| <i>Beam Inclination</i> | 42° |

Illuminance


Accessories

Standard Power Supply




| | |
|-----------------|-------------------|
| <i>Code</i> | 026.220 |
| <i>Measures</i> | 84x57x30mm |
| <i>Power</i> | min11,6W max34,7W |
| <i>Input</i> | 90-264 V~W |
| <i>Output</i> | 1050mA |

Dimmable Power Supply



| | |
|-----------------|-------------|
| <i>Code</i> | 026.206 |
| <i>Measures</i> | 124x82x23mm |
| <i>Power</i> | 59,9W |
| <i>Input</i> | 180-295V~W |
| <i>Output</i> | 1050mA |
| <i>Dimmable</i> | PUSH/DALI |




| | |
|-----------------|-------------|
| <i>Code</i> | 026.207 |
| <i>Measures</i> | 124x82x23mm |
| <i>Power</i> | 59,9W |
| <i>Input</i> | 180-295V~W |
| <i>Output</i> | 1050mA |
| <i>Dimmable</i> | 0-10V |

Other Accessories

Code M900A-00
Description Subwoofer with frequency
Notes

Code M900B-00
Description Subwoofer with audio in
Notes

Code M900C-00
Description Subwoofer with audio
Notes



Code 099.142
Description Emergency Kit
Notes