


# Technical Data Sheet

Last data update


3/15/2016

9010  
novantadieci®




*Req. space behind the plasterboard*

115mm




*hole on the plasterboard*

315x165mm




*External measures*

310x160mm




*Measures of the light output*

77x77mm



*Height without electrical part*

90mm



*Height including the electrical part*

110mm

## Notes on measures

## General notes

## SONORE

M004A-35

Sonore recessed spotlight / CRISTALY

Surface finish : CRISTALY

GU10 ø50 MAX 2x35W / 240V

### Model

Code	M004A
Product family	SONORE
Type	Sonore recessed spotlight

### Material/Surface finish

Code	004
Material	CRISTALY
Surface finish	CRISTALY

### Electrical part

Code	35
Type	GU10 ø50
Power	MAX 2x35W
Tension	240V
Light Output	-----
Colour Temperature	-----
CRI	-----

### Dati sistema Sonore

N° Driver	2
Impedenza	8 Ohm
Potenza nominale	40 Wrms
Potenza di picco	80 Wmax
Sensibilità	85 dB/oct
Risposta in Frequenza	200-20000 Hz
Input	da centralina M900

### General Data

Protection Index	IP20
Isolation Class	II
Cover	
Weight [Kg]	2,4
Country of production	MADE IN ITALY
Mounting instruction	025.536_9010_REV01

### Installation

Multisize system	SI
Position	Wall/Ceiling lighting

### Packaging

Type	White american Box
Measures AxBxH	425x220x130mm
Gross Weight [Kg]	2,6492

Master carton	NO
Quantity of articles	
Measures AxBxH	

# Technical Data Sheet

9010  
novantadieci®

M004A-35

## Fotometric Data

<i>Electrical part</i>			
<i>Power</i>			
<i>Light Output</i>	lm		
<i>Colour Temperature</i>			
<i>CRI</i>			
<i>Lamp Light Output</i>	%		
<i>Light Output of the lamp</i>			
<i>Beam Angle</i>			
<i>Beam Inclination</i>			

## Accessories

### LED bulbs



<i>Code</i>	L001-3018
<i>Power</i>	8W
<i>Tension</i>	220-240V
<i>Flux</i>	650lm
<i>CRI</i>	85
<i>Colour Temperature</i>	3000°K
<i>Beam Angle</i>	60°

<i>Code</i>	L002-3020
<i>Power</i>	8W
<i>Tension</i>	220-240V
<i>Flux</i>	650lm
<i>CRI</i>	85
<i>Colour Temperature</i>	3000°K
<i>Beam Angle</i>	30°

<i>Code</i>	L003-3022
<i>Power</i>	12W
<i>Tension</i>	220-240V
<i>Flux</i>	1000lm
<i>CRI</i>	85
<i>Colour Temperature</i>	3000°K
<i>Beam Angle</i>	60°

<i>Code</i>	L004-3018
<i>Power</i>	12W
<i>Tension</i>	220-240V
<i>Flux</i>	1000lm
<i>CRI</i>	85
<i>Colour Temperature</i>	3000°K
<i>Beam Angle</i>	30°

### Other Accessories

<i>Code</i>	M900A-00
<i>Description</i>	Subwoofer with frequen
<i>Notes</i>	

<i>Code</i>	M900B-00
<i>Description</i>	Subwoofer with audio in
<i>Notes</i>	

<i>Code</i>	M900C-00
<i>Description</i>	Subwoofer with audio
<i>Notes</i>	

<i>Code</i>	021.231
<i>Description</i>	GU5.3 Lampholder
<i>Notes</i>	