


# Technical Data Sheet

Last data update


4/26/16

9010  
novantadieci®




*Req. space behind the plasterboard*

170mm




*hole on the plasterboard*

255x255mm




*External measures*

250x250mm




*Measures of the light output*

150x150mm



*Height without electrical part*

110mm



*Height including the electrical part*

165mm

## Notes on measures

## General notes

## SONORE

M006-4008

Recessed Spotlight / CRISTALY

Surface finish : CRISTALY

LED 13W / 700mA / 1700lm / 4000°K / CRI85

## Model

Code	M006
Product family	SONORE
Type	Recessed Spotlight

## Material/Surface finish

Code	004
Material	CRISTALY
Surface finish	CRISTALY

## Electrical part

Code	4008
Type	LED
Power	13W
Current	700mA
Light Output	1700lm
Colour Temperature	4000°K
CRI	85

## Dati sistema Sonore

N° Driver	2
Impedenza	8 Ohm
Potenza nominale	40 Wrms
Potenza di picco	80 Wmax
Sensibilità	85 dB/oct
Risposta in Frequenza	200-20000 Hz
Input	da centralina M900

## General Data

Protection Index	IP20
Isolation Class	III
Cover	Satin Polycarbonate
Weight [Kg]	2,55
Country of production	MADE IN ITALY
Mounting instruction	025.535_9010_REV02

## Installation

Multisize system	SI
Position	Ceiling

## Packaging


Type	White american Box
Measures AxBxH	440x435x210mm
Gross Weight [Kg]	3,374

Master carton	NO
Quantity of articles	
Measures AxBxH	

# Technical Data Sheet

M006-4008

## Fotometric Data




<i>Electrical part</i>	4008
<i>Power</i>	13W
<i>Light Output</i>	1700lm
<i>Colour Temperature</i>	4000°K
<i>CRI</i>	85
<i>Lamp Light Output</i>	68%
<i>Light Output of the lamp</i>	1156lm
<i>Beam Angle</i>	51°
<i>Beam Inclination</i>	0°


<i>Illuminance</i>	1m	1277lux
	2m	319lux
	3m	142lux
	4m	80lux
	5m	51lux

## Accessories

### Standard Power Supply




<i>Code</i>	026.255
<i>Measures</i>	88,5x41x23mm
<i>Power</i>	min11,9W max18,2W
<i>Input</i>	220-240V~W
<i>Output</i>	700mA




<i>Code</i>	026.256
<i>Measures</i>	118x42,5x24mm
<i>Power</i>	min25,2W max35,7W
<i>Input</i>	220-240V~W
<i>Output</i>	700mA


### Dimmable Power Supply



<i>Code</i>	026.219
<i>Measures</i>	155x51x26mm
<i>Power</i>	19,6W
<i>Input</i>	220-240V~W
<i>Output</i>	700mA
<i>Dimmable</i>	PUSH/0-10V/DALI



<i>Code</i>	026.206
<i>Measures</i>	124x82x23mm
<i>Power</i>	60,2W
<i>Input</i>	180-295V~W
<i>Output</i>	700mA
<i>Dimmable</i>	PUSH/DALI




<i>Code</i>	026.207
<i>Measures</i>	124x82x23mm
<i>Power</i>	60,2W
<i>Input</i>	180-295V~W
<i>Output</i>	700mA
<i>Dimmable</i>	0-10V

## Other Accessories

<i>Code</i>	M900A-00
<i>Description</i>	Subwoofer with frequ
<i>Notes</i>	

<i>Code</i>	M900B-00
<i>Description</i>	Subwoofer with audio in
<i>Notes</i>	

<i>Code</i>	M900C-00
<i>Description</i>	Subwoofer with audio
<i>Notes</i>	



<i>Code</i>	099.142
<i>Description</i>	Emergency Kit
<i>Notes</i>	