


Technical Data Sheet

Last data update


3/15/2016

9010
novantadieci®




Req. space behind the plasterboard

15mm




hole on the plasterboard

295x255mm



External measures

290x250mm



Measures of the light output

180x90mm



Height without electrical part

25mm



Height including the electrical part

25mm

Notes on measures

General notes

15MM

4193D-4026

Recessed Spotlight / CRISTALY

Surface finish : CRISTALY

LED 16W / 350mA / 2330lm / 4000°K / CRI85

Model

| | |
|----------------|--------------------|
| Code | 4193D |
| Product family | 15MM |
| Type | Recessed Spotlight |

Material/Surface finish

| | |
|----------------|----------|
| Code | 004 |
| Material | CRISTALY |
| Surface finish | CRISTALY |

Electrical part

| | |
|--------------------------|------------------------|
| Code | 4026 |
| Type | LED |
| Power | 16W |
| Current | 350mA |
| Light Output | 2330lm |
| Colour Temperature | 4000°K |
| CRI | 85 |
| Light Output of the lamp | 1467,9lm |
| Dimmable | SI |
| Power Supply | by Remote Power Supply |
| Connection | 2 PVC cables |
| Cover | Etched Glass |

General Data

| | |
|-----------------------|--------------------|
| Protection Index | IP20-IP44 |
| Isolation Class | III |
| Weight [Kg] | 1,7 |
| Country of production | MADE IN ITALY |
| Mounting instruction | 025.409_9010_REV04 |

Installation

| | |
|------------------|-----------------------|
| Multisize system | NO |
| Position | Wall/Ceiling lighting |


Packaging

| | |
|----------------------|--------------------|
| Type | White american Box |
| Measures AxBxH | 310x80x465mm |
| Gross Weight [Kg] | 1,9364 |
| Master carton | NO |
| Quantity of articles | |
| Measures AxBxH | |

Technical Data Sheet

4193D-4026

Fotometric Data




| | |
|---------------------------------|----------|
| <i>Electrical part</i> | 4026 |
| <i>Power</i> | 16W |
| <i>Light Output</i> | 2330lm |
| <i>Colour Temperature</i> | 4000°K |
| <i>CRI</i> | 85 |
| <i>Lamp Light Output</i> | 63% |
| <i>Light Output of the lamp</i> | 1467,9lm |
| <i>Beam Angle</i> | 96° |
| <i>Beam Inclination</i> | 0° |

| | | |
|--------------------|----|--------|
| <i>Illuminance</i> | 1m | 633lux |
| | 2m | 158lux |
| | 3m | 70lux |
| | 4m | 40lux |
| | 5m | 25lux |


Accessories

Standard Power Supply




| | |
|-----------------|-------------------|
| <i>Code</i> | 026.252 |
| <i>Measures</i> | 88,5x41x23mm |
| <i>Power</i> | min12,6W max18,2W |
| <i>Input</i> | 220-240V~W |
| <i>Output</i> | 350mA |


Dimmable Power Supply



| | |
|-----------------|-----------------|
| <i>Code</i> | 026.219 |
| <i>Measures</i> | 155x51x26mm |
| <i>Power</i> | 16,1W |
| <i>Input</i> | 220-240V~W |
| <i>Output</i> | 350mA |
| <i>Dimmable</i> | PUSH/0-10V/DALI |




| | |
|-----------------|----------------|
| <i>Code</i> | 026.185 |
| <i>Measures</i> | 124x82x23mm |
| <i>Power</i> | min0,7W max35W |
| <i>Input</i> | 180-295V~W |
| <i>Output</i> | 350mA |
| <i>Dimmable</i> | PUSH/DALI |



| | |
|-----------------|----------------|
| <i>Code</i> | 026.187 |
| <i>Measures</i> | 124x82x23mm |
| <i>Power</i> | min0,7W max35W |
| <i>Input</i> | 180-295V~W |
| <i>Output</i> | 350mA |
| <i>Dimmable</i> | 0-10V |

Other Accessories



| | |
|--------------------|---------------|
| <i>Code</i> | 099.142 |
| <i>Description</i> | Emergency Kit |
| <i>Notes</i> | |