


Technical Data Sheet

Last data update


1/17/2017

9010
novantadieci®




Req. space behind the plasterboard

110mm




hole on the plasterboard

205x205mm



External measures

200x200mm




Measures of the light output

120x120mm



Height without electrical part

55mm



Height including the electrical part

105mm

Notes on measures

General notes

INCASSO A PLAFONE E PARETE

4045C-2708

Recessed Spotlight / CRISTALY

Surface finish : CRISTALY

LED 13W / 700mA / 1500lm / 2700°K / CRI85

Model

Code	4045C
Product family	INCASSO A PLAFONE E PARETE
Type	Recessed Spotlight

Material/Surface finish

Code	004
Material	CRISTALY
Surface finish	CRISTALY

Electrical part

Code	2708
Type	LED
Power	13W
Current	700mA
Light Output	1500lm
Colour Temperature	2700°K
CRI	85

Light Output of the lamp	1215lm
Dimmable	SI

Power Supply	Power Supply in counterceiling
Connection	2 PVC cables
Cover	

General Data

Protection Index	IP20
Isolation Class	III
Weight [Kg]	1,65
Country of production	MADE IN ITALY
Mounting instruction	025.552_9010_REV03

Installation

Multisize system	SI
Position	Wall/Ceiling lighting

Packaging


Type	White american Box
Measures AxBxH	440x435x210mm
Gross Weight [Kg]	2,474
Master carton	NO
Quantity of articles	
Measures AxBxH	

Technical Data Sheet

4045C-2708

9010
novantadieci®

Fotometric Data




<i>Electrical part</i>	2708
<i>Power</i>	13W
<i>Light Output</i>	1500lm
<i>Colour Temperature</i>	2700°K
<i>CRI</i>	85
<i>Lamp Light Output</i>	81%
<i>Light Output of the lamp</i>	1215lm
<i>Beam Angle</i>	44°
<i>Beam Inclination</i>	

<i>Illuminance</i>	1m	1615lux
	2m	404lux
	3m	179lux
	4m	101lux
	5m	65lux


Accessories

Housing Box for Brickwork




<i>Code</i>	023.447
<i>Measures</i>	200X200X120mm
<i>Measures of the hole on</i>	230X230X130mm

Standard Power Supply




<i>Code</i>	026.255
<i>Measures</i>	88,5x41x23mm
<i>Power</i>	min11,9W max18,2W
<i>Input</i>	220-240V~W
<i>Output</i>	700mA




<i>Code</i>	026.256
<i>Measures</i>	118x42,5x24mm
<i>Power</i>	min25,2W max35,7W
<i>Input</i>	220-240V~W
<i>Output</i>	700mA


Dimmable Power Supply



<i>Code</i>	026.219
<i>Measures</i>	155x51x26mm
<i>Power</i>	19,6W
<i>Input</i>	220-240V~W
<i>Output</i>	700mA
<i>Dimmable</i>	PUSH/0-10V/DALI



<i>Code</i>	026.206
<i>Measures</i>	124x82x23mm
<i>Power</i>	60,2W
<i>Input</i>	180-295V~W
<i>Output</i>	700mA
<i>Dimmable</i>	PUSH/DALI




<i>Code</i>	026.207
<i>Measures</i>	124x82x23mm
<i>Power</i>	60,2W
<i>Input</i>	180-295V~W
<i>Output</i>	700mA
<i>Dimmable</i>	0-10V

Technical Data Sheet

4045C-2708

Accessories

Other Accessories



Code	099.142
Description	Emergency Kit
Notes	