


Technical Data Sheet

Last data update


8/5/2017

9010
novantadieci®



Base

1200mm



Height

40mm




Depth

60mm




Req. space behind the plasterboard

50mm




hole on the plasterboard

140*x140*mm



External measures

135*x135*mm



General notes

INCASSO DA PARETE

2486D-3003

Recessed Wall lamp / CRISTALY + ALUMITE

Surface finish : CRISTALY

LED 32W / 24Vdc / 3600lm / 3000°K / CRI85

Model

| | |
|----------------|--------------------|
| Code | 2486D |
| Product family | INCASSO DA PARETE |
| Type | Recessed Wall lamp |

Material/Surface finish

| | |
|----------------|--------------------|
| Code | 004 |
| Material | CRISTALY + ALUMITE |
| Surface finish | CRISTALY |

Electrical part

| | |
|--------------------------|------------------------|
| Code | 3003 |
| Type | LED |
| Power | 32W |
| Tension | 24Vdc |
| Light Output | 3600lm |
| Colour Temperature | 3000°K |
| CRI | 85 |
| Light Output of the lamp | 2520lm |
| Dimmable | SI |
| Power Supply | by Remote Power Supply |
| Connection | Screw Terminal |
| Cover | |

General Data

| | |
|-----------------------|---------------|
| Protection Index | IP20 |
| Isolation Class | III |
| Weight [Kg] | 1,9 |
| Country of production | MADE IN ITALY |
| Mounting instruction | 025.585_9010 |

Installation

| | |
|------------------|-----------|
| Multisize system | SI |
| Position | Wall Lamp |

Packaging


| | |
|----------------------|--------------------|
| Type | White american Box |
| Measures AxBxH | 240x1310x170mm |
| Gross Weight [Kg] | 2,9957 |
| Master carton | NO |
| Quantity of articles | |
| Measures AxBxH | |

Technical Data Sheet

2486D-3003

9010
novantadieci®

Fotometric Data



| | |
|---------------------------------|---------|
| <i>Electrical part</i> | 3003_32 |
| <i>Power</i> | 32W |
| <i>Light Output</i> | 3600lm |
| <i>Colour Temperature</i> | 3000°K |
| <i>CRI</i> | 85 |
| | |
| <i>Lamp Light Output</i> | 70% |
| <i>Light Output of the lamp</i> | 2520lm |
| <i>Beam Angle</i> | 115° |
| <i>Beam Inclination</i> | |

Illuminance


Accessories

Housing Box for Brickwork



Code 023.478
Measures 140X140X75mm
Measures of the hole on 170X170X85mm


Standard Power Supply




Code 026.259
Measures 167x45x30mm
Power 36W
Input 220-240V~W
Output 24Vdc



Code 026.260
Measures 157x54x36mm
Power 60W
Input 220-240V~W
Output 24Vdc




Code 026.261
Measures 219x63x35.5mm
Power 150W
Input 180-295V~W
Output 24Vdc




Code 026.262
Measures 244x71x35.5mm
Power 240W
Input 180-295V~W
Output 24Vdc


Dimmable Power Supply



Code 026.209
Measures 125x82x29mm
Power 60W
Input 220-240 V~W
Output 24Vdc
Dimmable PUSH/1-10V



Code 026.190+026.261
Measures 156x52x24mm
Power 150W
Input 180-295V~W
Output 24Vdc
Dimmable PUSH/0-10V/DALI



Code 026.190+026.262
Measures 156x52x24mm
Power 240W
Input 180-295V~W
Output 24Vdc
Dimmable PUSH/0-10V/DALI

Technical Data Sheet

2486D-3003

9010
novantadieci®

Accessories

Other Accessories



| | |
|--------------------|---------------|
| <i>Code</i> | 099.142 |
| <i>Description</i> | Emergency Kit |
| <i>Notes</i> | |