


Technical Data Sheet

Last data update


8/5/2017

9010
novantadieci®



Base

2000mm



Height

40mm




Depth

60mm




Req. space behind the plasterboard

50mm




hole on the plasterboard

140*x140*mm



External measures

135*x135*mm



General notes

INCASSO DA PARETE

2486F-2703

Recessed Wall lamp / CRISTALY + ALUMITE

Surface finish : CRISTALY

LED 52W / 24Vdc / 5700lm / 2700°K / CRI85

Model

| | |
|----------------|--------------------|
| Code | 2486F |
| Product family | INCASSO DA PARETE |
| Type | Recessed Wall lamp |

Material/Surface finish

| | |
|----------------|--------------------|
| Code | 004 |
| Material | CRISTALY + ALUMITE |
| Surface finish | CRISTALY |

Electrical part

| | |
|--------------------------|------------------------|
| Code | 2703 |
| Type | LED |
| Power | 52W |
| Tension | 24Vdc |
| Light Output | 5700lm |
| Colour Temperature | 2700°K |
| CRI | 85 |
| Light Output of the lamp | 3990lm |
| Dimmable | SI |
| Power Supply | by Remote Power Supply |
| Connection | Screw Terminal |
| Cover | |

General Data

| | |
|-----------------------|---------------|
| Protection Index | IP20 |
| Isolation Class | III |
| Weight [Kg] | 2,4 |
| Country of production | MADE IN ITALY |
| Mounting instruction | 025.585_9010 |

Installation

| | |
|------------------|-----------|
| Multisize system | SI |
| Position | Wall Lamp |


Packaging

| | |
|----------------------|--------------------|
| Type | White american Box |
| Measures AxBxH | 200x2100x200mm |
| Gross Weight [Kg] | 4,122 |
| Master carton | NO |
| Quantity of articles | |
| Measures AxBxH | |

Technical Data Sheet

2486F-2703

Fotometric Data




| | |
|---------------------------------|---------|
| <i>Electrical part</i> | 2703_52 |
| <i>Power</i> | 52W |
| <i>Light Output</i> | 5700lm |
| <i>Colour Temperature</i> | 2700°K |
| <i>CRI</i> | 85 |
| <i>Lamp Light Output</i> | 70% |
| <i>Light Output of the lamp</i> | 3990lm |
| <i>Beam Angle</i> | 115° |
| <i>Beam Inclination</i> | |

Illuminance


Accessories

Housing Box for Brickwork




| | |
|--------------------------------|--------------|
| <i>Code</i> | 023.478 |
| <i>Measures</i> | 140X140X75mm |
| <i>Measures of the hole on</i> | 170X170X85mm |


Standard Power Supply



| | |
|-----------------|-------------|
| <i>Code</i> | 026.260 |
| <i>Measures</i> | 157x54x36mm |
| <i>Power</i> | 60W |
| <i>Input</i> | 220-240V~W |
| <i>Output</i> | 24Vdc |




| | |
|-----------------|---------------|
| <i>Code</i> | 026.261 |
| <i>Measures</i> | 219x63x35.5mm |
| <i>Power</i> | 150W |
| <i>Input</i> | 180-295V~W |
| <i>Output</i> | 24Vdc |




| | |
|-----------------|---------------|
| <i>Code</i> | 026.262 |
| <i>Measures</i> | 244x71x35.5mm |
| <i>Power</i> | 240W |
| <i>Input</i> | 180-295V~W |
| <i>Output</i> | 24Vdc |


Dimmable Power Supply



| | |
|-----------------|-------------|
| <i>Code</i> | 026.209 |
| <i>Measures</i> | 125x82x29mm |
| <i>Power</i> | 60W |
| <i>Input</i> | 220-240 V~W |
| <i>Output</i> | 24Vdc |
| <i>Dimmable</i> | PUSH/1-10V |



| | |
|-----------------|-----------------|
| <i>Code</i> | 026.190+026.261 |
| <i>Measures</i> | 156x52x24mm |
| <i>Power</i> | 150W |
| <i>Input</i> | 180-295V~W |
| <i>Output</i> | 24Vdc |
| <i>Dimmable</i> | PUSH/0-10V/DALI |



| | |
|-----------------|-----------------|
| <i>Code</i> | 026.190+026.262 |
| <i>Measures</i> | 156x52x24mm |
| <i>Power</i> | 240W |
| <i>Input</i> | 180-295V~W |
| <i>Output</i> | 24Vdc |
| <i>Dimmable</i> | PUSH/0-10V/DALI |

Technical Data Sheet

2486F-2703

9010
novantadieci®

Accessories

Other Accessories



| | |
|--------------------|---------------|
| <i>Code</i> | 099.142 |
| <i>Description</i> | Emergency Kit |
| <i>Notes</i> | |