

# Technical Data Sheet

Last data update


8/5/2017

9010  
novantadieci®



*Base*

2000mm



*Height*

40mm




*Depth*

60mm




*Req. space behind the plasterboard*

50mm



*hole on the plasterboard*

140\*x140\*mm



*External measures*

135\*x135\*mm



**General notes**

## INCASSO DA PARETE

2486F-3003

Recessed Wall lamp / CRISTALY + ALUMITE

Surface finish : CRISTALY

LED 52W / 24Vdc / 6000lm / 3000°K / CRI85

### Model

Code	2486F
Product family	INCASSO DA PARETE
Type	Recessed Wall lamp

### Material/Surface finish

Code	004
Material	CRISTALY + ALUMITE
Surface finish	CRISTALY

### Electrical part

Code	3003
Type	LED
Power	52W
Tension	24Vdc
Light Output	6000lm
Colour Temperature	3000°K
CRI	85
Light Output of the lamp	4200lm
Dimmable	SI
Power Supply	by Remote Power Supply
Connection	Screw Terminal
Cover	

### General Data

Protection Index	IP20
Isolation Class	III
Weight [Kg]	2,4
Country of production	MADE IN ITALY
Mounting instruction	025.585_9010

### Installation

Multisize system	SI
Position	Wall Lamp


### Packaging

Type	White american Box
Measures AxBxH	200x2100x200mm
Gross Weight [Kg]	4,122
Master carton	NO
Quantity of articles	
Measures AxBxH	

# Technical Data Sheet

2486F-3003

## Fotometric Data




<i>Electrical part</i>	3003_52
<i>Power</i>	52W
<i>Light Output</i>	6000lm
<i>Colour Temperature</i>	3000°K
<i>CRI</i>	85
<i>Lamp Light Output</i>	70%
<i>Light Output of the lamp</i>	4200lm
<i>Beam Angle</i>	115°
<i>Beam Inclination</i>	

### Illuminance


## Accessories

### Housing Box for Brickwork




<i>Code</i>	023.478
<i>Measures</i>	140X140X75mm
<i>Measures of the hole on</i>	170X170X85mm


## Standard Power Supply



<i>Code</i>	026.260
<i>Measures</i>	157x54x36mm
<i>Power</i>	60W
<i>Input</i>	220-240V~W
<i>Output</i>	24Vdc




<i>Code</i>	026.261
<i>Measures</i>	219x63x35.5mm
<i>Power</i>	150W
<i>Input</i>	180-295V~W
<i>Output</i>	24Vdc




<i>Code</i>	026.262
<i>Measures</i>	244x71x35.5mm
<i>Power</i>	240W
<i>Input</i>	180-295V~W
<i>Output</i>	24Vdc


## Dimmable Power Supply



<i>Code</i>	026.209
<i>Measures</i>	125x82x29mm
<i>Power</i>	60W
<i>Input</i>	220-240 V~W
<i>Output</i>	24Vdc
<i>Dimmable</i>	PUSH/1-10V



<i>Code</i>	026.190+026.261
<i>Measures</i>	156x52x24mm
<i>Power</i>	150W
<i>Input</i>	180-295V~W
<i>Output</i>	24Vdc
<i>Dimmable</i>	PUSH/0-10V/DALI



<i>Code</i>	026.190+026.262
<i>Measures</i>	156x52x24mm
<i>Power</i>	240W
<i>Input</i>	180-295V~W
<i>Output</i>	24Vdc
<i>Dimmable</i>	PUSH/0-10V/DALI

# Technical Data Sheet

2486F-3003

9010  
novantadieci®


---

## Accessories

---

### Other Accessories

---



<i>Code</i>	099.142
<i>Description</i>	Emergency Kit
<i>Notes</i>	