

# Technical Data Sheet

Last data update

7/16/2016

9010  
novantadieci®



|           |   |
|-----------|---|
|           | <u>Req. space behind the plasterboard</u> |
| 65mm      |   |
|           | <u>hole on the plasterboard</u>           |
| 355x305mm |   |
|           | <u>External measures</u>                  |
| 350x300mm |   |
|           | <u>Measures of the wall lamp</u>          |
| 300x240mm |   |
|           | <u>Height without electrical part</u>     |
| 25mm      |   |
|           | <u>Protrusion</u>                         |
| 85mm      |   |
|           |   |

## General notes

## INCASSO DA PARETE

2369A-4008

Recessed Wall lamp / CRISTALY  
Surface finish : CRISTALY  
LED 13W / 700mA / 1700lm / 4000°K / CRI85

### Model

|                |                    |
|----------------|--------------------|
| Code           | 2369A              |
| Product family | INCASSO DA PARETE  |
| Type           | Recessed Wall lamp |

### Material/Surface finish

|                |          |
|----------------|----------|
| Code           | 004      |
| Material       | CRISTALY |
| Surface finish | CRISTALY |

### Electrical part

|                          |                           |
|--------------------------|---------------------------|
| Code                     | 4008                      |
| Type                     | LED                       |
| Power                    | 13W                       |
| Current                  | 700mA                     |
| Light Output             | 1700lm                    |
| Colour Temperature       | 4000°K                    |
| CRI                      | 85                        |
| Light Output of the lamp | 833lm                     |
| Dimmable                 | SI                        |
| Power Supply             | by Remote Power Supply    |
| Connection               | 2 PVC cables              |
| Cover                    | Transparent Polycarbonate |

### General Data

|                       |                    |
|-----------------------|--------------------|
| Protection Index      | IP20               |
| Isolation Class       | III                |
| Weight [Kg]           | 3                  |
| Country of production | MADE IN ITALY      |
| Mounting instruction  | 025.550_9010_REV02 |

### Installation

|                  |           |
|------------------|-----------|
| Multisize system | SI        |
| Position         | Wall Lamp |


### Packaging

|                      |                    |
|----------------------|--------------------|
| Type                 | White american Box |
| Measures AxBxH       | 530x400x175mm      |
| Gross Weight [Kg]    | 3,7606             |
| Master carton        | NO                 |
| Quantity of articles |                    |
| Measures AxBxH       |                    |

# Technical Data Sheet

2369A-4008

## Fotometric Data




|                                 |        |
|---------------------------------|--------|
| <i>Electrical part</i>          | 4008   |
| <i>Power</i>                    | 13W    |
| <i>Light Output</i>             | 1700lm |
| <i>Colour Temperature</i>       | 4000°K |
| <i>CRI</i>                      | 85     |
| <i>Lamp Light Output</i>        | 49%    |
| <i>Light Output of the lamp</i> | 833lm  |
| <i>Beam Angle</i>               | 56°    |
| <i>Beam Inclination</i>         | 24°    |

### Illuminance


## Accessories

### Housing Box for Brickwork




|                                |              |
|--------------------------------|--------------|
| <i>Code</i>                    | 023.476      |
| <i>Measures</i>                | 355X305X50mm |
| <i>Measures of the hole on</i> | 385X335X60mm |

## Standard Power Supply




|                 |                   |
|-----------------|-------------------|
| <i>Code</i>     | 026.255           |
| <i>Measures</i> | 88,5x41x23mm      |
| <i>Power</i>    | min11,9W max18,2W |
| <i>Input</i>    | 220-240V~W        |
| <i>Output</i>   | 700mA             |




|                 |                   |
|-----------------|-------------------|
| <i>Code</i>     | 026.256           |
| <i>Measures</i> | 118x42,5x24mm     |
| <i>Power</i>    | min25,2W max35,7W |
| <i>Input</i>    | 220-240V~W        |
| <i>Output</i>   | 700mA             |


## Dimmable Power Supply



|                 |                 |
|-----------------|-----------------|
| <i>Code</i>     | 026.219         |
| <i>Measures</i> | 155x51x26mm     |
| <i>Power</i>    | 19,6W           |
| <i>Input</i>    | 220-240V~W      |
| <i>Output</i>   | 700mA           |
| <i>Dimmable</i> | PUSH/0-10V/DALI |




|                 |             |
|-----------------|-------------|
| <i>Code</i>     | 026.206     |
| <i>Measures</i> | 124x82x23mm |
| <i>Power</i>    | 60,2W       |
| <i>Input</i>    | 180-295V~W  |
| <i>Output</i>   | 700mA       |
| <i>Dimmable</i> | PUSH/DALI   |



|                 |             |
|-----------------|-------------|
| <i>Code</i>     | 026.207     |
| <i>Measures</i> | 124x82x23mm |
| <i>Power</i>    | 60,2W       |
| <i>Input</i>    | 180-295V~W  |
| <i>Output</i>   | 700mA       |
| <i>Dimmable</i> | 0-10V       |

## Accessories

### Other Accessories



*Code* 099.142  
*Description* Emergency Kit  
*Notes*



*Code* L007  
*Description* 20-240V  
*Notes*

*Code* 021.226  
*Description* GU4 Lampholder  
*Notes*