







# Technical Data Sheet

Last data update

3/15/2016

9010  
novantadieci®



## Notes on measures

## General notes

## INCASSO A PLAFONE E PARETE

4046-2725

Recessed lighting / CRISTALY  
Surface finish : CRISTALY  
LED 16W / 700mA / 2090lm / 2700°K / CRI85

### Model

Code	4046
Product family	INCASSO A PLAFONE E PARETE
Type	Recessed lighting

### Material/Surface finish

Code	004
Material	CRISTALY
Surface finish	CRISTALY

### Electrical part

Code	2725
Type	LED
Power	16W
Current	700mA
Light Output	2090lm
Colour Temperature	2700°K
CRI	85
Light Output of the lamp	1463lm
Dimmable	SI
Power Supply	Power Supply in counterceiling
Connection	2 PVC cables
Cover	Etched Glass

### General Data

Protection Index	IP20
Isolation Class	III
Weight [Kg]	3
Country of production	MADE IN ITALY
Mounting instruction	025.493_9010_REV03

### Installation

Multisize system	SI
Position	Wall/Ceiling lighting


### Packaging

Type	White american Box
Measures AxBxH	440x345x275mm
Gross Weight [Kg]	3,8558
Master carton	NO
Quantity of articles	
Measures AxBxH	

# Technical Data Sheet

4046-2725

## Fotometric Data




<i>Electrical part</i>	2725
<i>Power</i>	16W
<i>Light Output</i>	2090lm
<i>Colour Temperature</i>	2700°K
<i>CRI</i>	85
<i>Lamp Light Output</i>	70%
<i>Light Output of the lamp</i>	1463lm
<i>Beam Angle</i>	76°
<i>Beam Inclination</i>	0°


<i>Illuminance</i>	1m	827lux
	2m	207lux
	3m	92lux
	4m	52lux
	5m	33lux

## Accessories

### Standard Power Supply




<i>Code</i>	026.255
<i>Measures</i>	88,5x41x23mm
<i>Power</i>	min11,9W max18,2W
<i>Input</i>	220-240V~W
<i>Output</i>	700mA




<i>Code</i>	026.256
<i>Measures</i>	118x42,5x24mm
<i>Power</i>	min25,2W max35,7W
<i>Input</i>	220-240V~W
<i>Output</i>	700mA


### Dimmable Power Supply



<i>Code</i>	026.219
<i>Measures</i>	155x51x26mm
<i>Power</i>	19,6W
<i>Input</i>	220-240V~W
<i>Output</i>	700mA
<i>Dimmable</i>	PUSH/0-10V/DALI




<i>Code</i>	026.206
<i>Measures</i>	124x82x23mm
<i>Power</i>	60,2W
<i>Input</i>	180-295V~W
<i>Output</i>	700mA
<i>Dimmable</i>	PUSH/DALI



<i>Code</i>	026.207
<i>Measures</i>	124x82x23mm
<i>Power</i>	60,2W
<i>Input</i>	180-295V~W
<i>Output</i>	700mA
<i>Dimmable</i>	0-10V

## Other Accessories



<i>Code</i>	099.142
<i>Description</i>	Emergency Kit
<i>Notes</i>	