





*Req. space behind the plasterboard*

115mm




*hole on the plasterboard*

190x190mm



*External measures*

185x185mm



*Measures of the light output*

120x120mm



*Height without electrical part*

105mm



*Height including the electrical part*

105mm

## Notes on measures

## General notes

## INCASSO A PLAFONE E PARETE

4053-4006

Recessed lighting / CRISTALY

Surface finish : CRISTALY

LED 6.5W / 350mA / 900lm / 4000°K / CRI85

### Model

Code	4053
Product family	INCASSO A PLAFONE E PARETE
Type	Recessed lighting

### Material/Surface finish

Code	004
Material	CRISTALY
Surface finish	CRISTALY

### Electrical part

Code	4006
Type	LED
Power	6.5W
Current	350mA
Light Output	900lm
Colour Temperature	4000°K
CRI	85
Light Output of the lamp	612lm
Dimmable	SI
Power Supply	Power Supply in counterceiling
Connection	2 PVC cables
Cover	Etched Glass

### General Data

Protection Index	IP20-IP44
Isolation Class	III
Weight [Kg]	1,65
Country of production	MADE IN ITALY
Mounting instruction	025.456_9010_REV03

### Installation

Multisize system	SI
Position	Wall lamp/Ceiling Lamp


### Packaging

Type	White american Box
Measures AxBxH	340x260x187mm
Gross Weight [Kg]	1,9889
Master carton	NO
Quantity of articles	
Measures AxBxH	

# Technical Data Sheet

4053-4006

## Fotometric Data




<i>Electrical part</i>	4006
<i>Power</i>	6.5W
<i>Light Output</i>	900lm
<i>Colour Temperature</i>	4000°K
<i>CRI</i>	85

<i>Illuminance</i>	<i>1m</i>	<i>336lux</i>
	<i>2m</i>	<i>84lux</i>
	<i>3m</i>	<i>37lux</i>
	<i>4m</i>	<i>21lux</i>
	<i>5m</i>	<i>13lux</i>

<i>Lamp Light Output</i>	68%
<i>Light Output of the lamp</i>	612lm
<i>Beam Angle</i>	77°
<i>Beam Inclination</i>	0°


## Accessories

### Housing Box for Brickwork




<i>Code</i>	023.414
<i>Measures</i>	185X205X105mm
<i>Measures of the hole on</i>	215X235X115mm

## Standard Power Supply




<i>Code</i>	026.251
<i>Measures</i>	88,5x41x23mm
<i>Power</i>	min6W max8,8W
<i>Input</i>	220-240V~W
<i>Output</i>	350mA




<i>Code</i>	026.252
<i>Measures</i>	88,5x41x23mm
<i>Power</i>	min12,6W max18,2W
<i>Input</i>	220-240V~W
<i>Output</i>	350mA


## Dimmable Power Supply



<i>Code</i>	026.219
<i>Measures</i>	155x51x26mm
<i>Power</i>	16,1W
<i>Input</i>	220-240V~W
<i>Output</i>	350mA
<i>Dimmable</i>	PUSH/0-10V/DALI



<i>Code</i>	026.185
<i>Measures</i>	124x82x23mm
<i>Power</i>	min0,7W max35W
<i>Input</i>	180-295V~W
<i>Output</i>	350mA
<i>Dimmable</i>	PUSH/DALI



<i>Code</i>	026.187
<i>Measures</i>	124x82x23mm
<i>Power</i>	min0,7W max35W
<i>Input</i>	180-295V~W
<i>Output</i>	350mA
<i>Dimmable</i>	0-10V

4053-4006


---

## Accessories

---

### Other Accessories

---



<i>Code</i>	099.142
<i>Description</i>	Emergency Kit
<i>Notes</i>	