



Req. space behind the plasterboard

75mm




hole on the plasterboard

205x175mm




External measures

200x170mm




Measures of the light output

90x90mm



Height without electrical part

40mm



Height including the electrical part

65mm

## Notes on measures

## General notes

## INCASSO A PLAFONE E PARETE

4105-2725

Recessed Spotlight / CRISTALY

Surface finish : CRISTALY

LED 16W / 700mA / 2090lm / 2700°K / CRI85

### Model

Code	4105
Product family	INCASSO A PLAFONE E PARETE
Type	Recessed Spotlight

### Material/Surface finish

Code	004
Material	CRISTALY
Surface finish	CRISTALY

### Electrical part

Code	2725
Type	LED
Power	16W
Current	700mA
Light Output	2090lm
Colour Temperature	2700°K
CRI	85
Light Output of the lamp	1316,7lm
Dimmable	SI
Power Supply	Power Supply in counterceiling
Connection	2 PVC cables
Cover	Etched Glass

### General Data

Protection Index	IP20-IP44
Isolation Class	III
Weight [Kg]	1,2
Country of production	MADE IN ITALY
Mounting instruction	025.490_9010_REV03

### Installation

Multisize system	SI
Position	Wall/Ceiling lighting


### Packaging

Type	White american Box
Measures AxBxH	360x295x140mm
Gross Weight [Kg]	1,5048
Master carton	NO
Quantity of articles	
Measures AxBxH	

# Technical Data Sheet

4105-2725

## Fotometric Data




<i>Electrical part</i>	2725
<i>Power</i>	16W
<i>Light Output</i>	2090lm
<i>Colour Temperature</i>	2700°K
<i>CRI</i>	85
<i>Lamp Light Output</i>	63%
<i>Light Output of the lamp</i>	1316,7lm
<i>Beam Angle</i>	96°
<i>Beam Inclination</i>	0°

<i>Illuminance</i>	<i>1m</i>	<i>567lux</i>
	<i>2m</i>	<i>142lux</i>
	<i>3m</i>	<i>63lux</i>
	<i>4m</i>	<i>35lux</i>
	<i>5m</i>	<i>23lux</i>


## Accessories

### Housing Box for Brickwork




*Code* 023.471  
*Measures* 175X205X75mm  
*Measures of the hole on* 205X235X85mm

### Standard Power Supply




*Code* 026.255  
*Measures* 88,5x41x23mm  
*Power* min11,9W max18,2W  
*Input* 220-240V~W  
*Output* 700mA




*Code* 026.256  
*Measures* 118x42,5x24mm  
*Power* min25,2W max35,7W  
*Input* 220-240V~W  
*Output* 700mA


### Dimmable Power Supply



*Code* 026.219  
*Measures* 155x51x26mm  
*Power* 19,6W  
*Input* 220-240V~W  
*Output* 700mA  
*Dimmable* PUSH/0-10V/DALI



*Code* 026.206  
*Measures* 124x82x23mm  
*Power* 60,2W  
*Input* 180-295V~W  
*Output* 700mA  
*Dimmable* PUSH/DALI



*Code* 026.207  
*Measures* 124x82x23mm  
*Power* 60,2W  
*Input* 180-295V~W  
*Output* 700mA  
*Dimmable* 0-10V


---

## Accessories

---

### Other Accessories

---



<i>Code</i>	099.142
<i>Description</i>	Emergency Kit
<i>Notes</i>	