



Req. space behind the plasterboard

75mm




hole on the plasterboard

205x175mm




External measures

200x170mm




Measures of the light output

90x90mm



Height without electrical part

40mm



Height including the electrical part

65mm

Notes on measures

General notes

INCASSO A PLAFONE E PARETE

4105-3025

Recessed Spotlight / CRISTALY

Surface finish : CRISTALY

LED 16W / 700mA / 2200lm / 3000°K / CRI85

Model

Code	4105
Product family	INCASSO A PLAFONE E PARETE
Type	Recessed Spotlight

Material/Surface finish

Code	004
Material	CRISTALY
Surface finish	CRISTALY

Electrical part

Code	3025
Type	LED
Power	16W
Current	700mA
Light Output	2200lm
Colour Temperature	3000°K
CRI	85
Light Output of the lamp	1386lm
Dimmable	SI
Power Supply	Power Supply in counterceiling
Connection	2 PVC cables
Cover	Etched Glass

General Data

Protection Index	IP20-IP44
Isolation Class	III
Weight [Kg]	1,2
Country of production	MADE IN ITALY
Mounting instruction	025.490_9010_REV03

Installation

Multisize system	SI
Position	Wall/Ceiling lighting


Packaging

Type	White american Box
Measures AxBxH	360x295x140mm
Gross Weight [Kg]	1,5048
Master carton	NO
Quantity of articles	
Measures AxBxH	

Technical Data Sheet

4105-3025

Fotometric Data




<i>Electrical part</i>	3025
<i>Power</i>	16W
<i>Light Output</i>	2200lm
<i>Colour Temperature</i>	3000°K
<i>CRI</i>	85

<i>Illuminance</i>	1m	597lux
	2m	149lux
	3m	66lux
	4m	37lux
	5m	24lux

<i>Lamp Light Output</i>	63%
<i>Light Output of the lamp</i>	1386lm
<i>Beam Angle</i>	96°
<i>Beam Inclination</i>	0°


Accessories

Housing Box for Brickwork




<i>Code</i>	023.471
<i>Measures</i>	175X205X75mm
<i>Measures of the hole on</i>	205X235X85mm

Standard Power Supply




<i>Code</i>	026.255
<i>Measures</i>	88,5x41x23mm
<i>Power</i>	min11,9W max18,2W
<i>Input</i>	220-240V~W
<i>Output</i>	700mA




<i>Code</i>	026.256
<i>Measures</i>	118x42,5x24mm
<i>Power</i>	min25,2W max35,7W
<i>Input</i>	220-240V~W
<i>Output</i>	700mA


Dimmable Power Supply



<i>Code</i>	026.219
<i>Measures</i>	155x51x26mm
<i>Power</i>	19,6W
<i>Input</i>	220-240V~W
<i>Output</i>	700mA
<i>Dimmable</i>	PUSH/0-10V/DALI




<i>Code</i>	026.206
<i>Measures</i>	124x82x23mm
<i>Power</i>	60,2W
<i>Input</i>	180-295V~W
<i>Output</i>	700mA
<i>Dimmable</i>	PUSH/DALI



<i>Code</i>	026.207
<i>Measures</i>	124x82x23mm
<i>Power</i>	60,2W
<i>Input</i>	180-295V~W
<i>Output</i>	700mA
<i>Dimmable</i>	0-10V

Accessories

Other Accessories



<i>Code</i>	099.142
<i>Description</i>	Emergency Kit
<i>Notes</i>	