



Req. space behind the plasterboard

140mm




hole on the plasterboard

305x305mm



External measures

300x300mm




Measures of the light output

ø130mm



Height without electrical part

55mm



Height including the electrical part

135mm

Notes on measures

General notes

INCASSO A PLAFONE

4110-2706

Recessed Spotlight / CRISTALY

Surface finish : CRISTALY

LED 6.5W / 350mA / 800lm / 2700°K / CRI85

Model

| | |
|----------------|--------------------|
| Code | 4110 |
| Product family | INCASSO A PLAFONE |
| Type | Recessed Spotlight |

Material/Surface finish

| | |
|----------------|----------|
| Code | 004 |
| Material | CRISTALY |
| Surface finish | CRISTALY |

Electrical part

| | |
|--------------------------|--------------------------------|
| Code | 2706 |
| Type | LED |
| Power | 6.5W |
| Current | 350mA |
| Light Output | 800lm |
| Colour Temperature | 2700°K |
| CRI | 85 |
| Light Output of the lamp | 600lm |
| Dimmable | SI |
| Power Supply | Power Supply in counterceiling |
| Connection | 2 PVC cables |
| Cover | Etched Glass |

General Data

| | |
|-----------------------|--------------------|
| Protection Index | IP20-IP44 |
| Isolation Class | III |
| Weight [Kg] | 2,5 |
| Country of production | MADE IN ITALY |
| Mounting instruction | 025.412_9010_REV03 |

Installation

| | |
|------------------|---------|
| Multisize system | SI |
| Position | Ceiling |


Packaging

| | |
|----------------------|--------------------|
| Type | White american Box |
| Measures AxBxH | 530x400x175mm |
| Gross Weight [Kg] | 3,2606 |
| Master carton | NO |
| Quantity of articles | |
| Measures AxBxH | |

Technical Data Sheet

4110-2706

Fotometric Data




| | |
|---------------------------|--------|
| <i>Electrical part</i> | 2706 |
| <i>Power</i> | 6.5W |
| <i>Light Output</i> | 800lm |
| <i>Colour Temperature</i> | 2700°K |
| <i>CRI</i> | 85 |

| | | |
|--------------------|-----------|---------------|
| <i>Illuminance</i> | <i>1m</i> | <i>398lux</i> |
| | <i>2m</i> | <i>100lux</i> |
| | <i>3m</i> | <i>44lux</i> |
| | <i>4m</i> | <i>25lux</i> |
| | <i>5m</i> | <i>16lux</i> |


| | |
|---------------------------------|-------|
| <i>Lamp Light Output</i> | 75% |
| <i>Light Output of the lamp</i> | 600lm |
| <i>Beam Angle</i> | 66° |
| <i>Beam Inclination</i> | 0° |

Accessories

Standard Power Supply




| | |
|-----------------|---------------|
| <i>Code</i> | 026.251 |
| <i>Measures</i> | 88,5x41x23mm |
| <i>Power</i> | min6W max8,8W |
| <i>Input</i> | 220-240V~W |
| <i>Output</i> | 350mA |




| | |
|-----------------|-------------------|
| <i>Code</i> | 026.252 |
| <i>Measures</i> | 88,5x41x23mm |
| <i>Power</i> | min12,6W max18,2W |
| <i>Input</i> | 220-240V~W |
| <i>Output</i> | 350mA |


Dimmable Power Supply



| | |
|-----------------|-----------------|
| <i>Code</i> | 026.219 |
| <i>Measures</i> | 155x51x26mm |
| <i>Power</i> | 16,1W |
| <i>Input</i> | 220-240V~W |
| <i>Output</i> | 350mA |
| <i>Dimmable</i> | PUSH/0-10V/DALI |




| | |
|-----------------|----------------|
| <i>Code</i> | 026.185 |
| <i>Measures</i> | 124x82x23mm |
| <i>Power</i> | min0,7W max35W |
| <i>Input</i> | 180-295V~W |
| <i>Output</i> | 350mA |
| <i>Dimmable</i> | PUSH/DALI |



| | |
|-----------------|----------------|
| <i>Code</i> | 026.187 |
| <i>Measures</i> | 124x82x23mm |
| <i>Power</i> | min0,7W max35W |
| <i>Input</i> | 180-295V~W |
| <i>Output</i> | 350mA |
| <i>Dimmable</i> | 0-10V |

Other Accessories



| | |
|--------------------|---------------|
| <i>Code</i> | 099.142 |
| <i>Description</i> | Emergency Kit |
| <i>Notes</i> | |