


Technical Data Sheet

Last data update


3/15/2016

9010
novantadieci®



Req. space behind the plasterboard

40(70*)mm



hole on the plasterboard

ø475mm



External measures

ø470mm



Measures of the light output

ø300mm



Height without electrical part

75mm



Protrusion

45mm



General notes

INCASSO A PLAFONE

4114-2713

Recessed lighting / CRISTALY

Surface finish : CRISTALY

LED 30W / 700mA / 3300lm / 2700°K / CRI85

Model

Code	4114
Product family	INCASSO A PLAFONE
Type	Recessed lighting

Material/Surface finish

Code	004
Material	CRISTALY
Surface finish	CRISTALY

Electrical part

Code	2713
Type	LED
Power	30W
Current	700mA
Light Output	3300lm
Colour Temperature	2700°K
CRI	85

Light Output of the lamp	2079lm
Dimmable	SI

Power Supply	Power Supply in counterceiling
Connection	Screw Terminal
Cover	Etched Glass

General Data

Protection Index	IP20-IP44
Isolation Class	III
Weight [Kg]	5,8
Country of production	MADE IN ITALY
Mounting instruction	025.494_9010_REV03

Installation

Multisize system	NO
Position	Ceiling


Packaging

Type	White american Box
Measures AxBxH	512x512x278mm
Gross Weight [Kg]	7,294
Master carton	NO
Quantity of articles	
Measures AxBxH	

Technical Data Sheet

4114-2713

Fotometric Data




<i>Electrical part</i>	2713
<i>Power</i>	30W
<i>Light Output</i>	3300lm
<i>Colour Temperature</i>	2700°K
<i>CRI</i>	85
<i>Lamp Light Output</i>	63%
<i>Light Output of the lamp</i>	2079lm
<i>Beam Angle</i>	101°
<i>Beam Inclination</i>	0°

<i>Illuminance</i>	1m	838lux
	2m	209lux
	3m	93lux
	4m	52lux
	5m	34lux


Accessories

Standard Power Supply




<i>Code</i>	026.256
<i>Measures</i>	118x42,5x24mm
<i>Power</i>	min25,2W max35,7W
<i>Input</i>	220-240V~W
<i>Output</i>	700mA

Dimmable Power Supply




<i>Code</i>	026.206
<i>Measures</i>	124x82x23mm
<i>Power</i>	60,2W
<i>Input</i>	180-295V~W
<i>Output</i>	700mA
<i>Dimmable</i>	PUSH/DALI



<i>Code</i>	026.207
<i>Measures</i>	124x82x23mm
<i>Power</i>	60,2W
<i>Input</i>	180-295V~W
<i>Output</i>	700mA
<i>Dimmable</i>	0-10V

Other Accessories



<i>Code</i>	099.142
<i>Description</i>	Emergency Kit
<i>Notes</i>	