

Technical Data Sheet

Last data update


3/15/2016

9010
novantadieci®



Req. space behind the plasterboard

40(70*)mm




hole on the plasterboard

ø475mm



External measures

ø470mm



Measures of the light output

ø300mm



Height without electrical part

75mm



Protrusion

45mm



General notes

INCASSO A PLAFONE

4114-4013

Recessed lighting / CRISTALY

Surface finish : CRISTALY

LED 30W / 700mA / 3700lm / 4000°K / CRI85

Model

Code	4114
Product family	INCASSO A PLAFONE
Type	Recessed lighting

Material/Surface finish

Code	004
Material	CRISTALY
Surface finish	CRISTALY

Electrical part

Code	4013
Type	LED
Power	30W
Current	700mA
Light Output	3700lm
Colour Temperature	4000°K
CRI	85

Light Output of the lamp	2331lm
Dimmable	SI

Power Supply	Power Supply in counterceiling
Connection	Screw Terminal
Cover	Etched Glass

General Data

Protection Index	IP20-IP44
Isolation Class	III
Weight [Kg]	5,8
Country of production	MADE IN ITALY
Mounting instruction	025.494_9010_REV03

Installation

Multisize system	NO
Position	Ceiling

Packaging


Type	White american Box
Measures AxBxH	512x512x278mm
Gross Weight [Kg]	7,294
Master carton	NO
Quantity of articles	
Measures AxBxH	

Technical Data Sheet

4114-4013

9010
novantadieci®

Fotometric Data




Electrical part	4013
Power	30W
Light Output	3700lm
Colour Temperature	4000°K
CRI	85

Illuminance	1m	939lux
	2m	235lux
	3m	104lux
	4m	59lux
	5m	38lux

Lamp Light Output	63%
Light Output of the lamp	2331lm
Beam Angle	101°
Beam Inclination	0°


Accessories

Standard Power Supply




Code	026.256
Measures	118x42,5x24mm
Power	min25,2W max35,7W
Input	220-240V~W
Output	700mA

Dimmable Power Supply




Code	026.206
Measures	124x82x23mm
Power	60,2W
Input	180-295V~W
Output	700mA
Dimmable	PUSH/DALI



Code	026.207
Measures	124x82x23mm
Power	60,2W
Input	180-295V~W
Output	700mA
Dimmable	0-10V

Other Accessories



Code	099.142
Description	Emergency Kit
Notes	