


Technical Data Sheet

Last data update


3/15/2016

9010
novantadieci®



Req. space behind the plasterboard

50(80*)mm



hole on the plasterboard

ø780mm



External measures

ø775mm



Measures of the light output

ø600mm



Height without electrical part

75mm



Protrusion

45mm



General notes

INCASSO A PLAFONE

4122-4015

Recessed lighting / CRISTALY

Surface finish : CRISTALY

LED 88W / 2x1050mA / 11000lm / 4000°K / CRI85

Model

Code	4122
Product family	INCASSO A PLAFONE
Type	Recessed lighting

Material/Surface finish

Code	004
Material	CRISTALY
Surface finish	CRISTALY

Electrical part

Code	4015
Type	LED
Power	88W
Current	2x1050mA
Light Output	11000lm
Colour Temperature	4000°K
CRI	85

Light Output of the lamp	7700lm
Dimmable	SI

Power Supply	Power Supply in counterceiling
Connection	Screw Terminal
Cover	Etched Glass

General Data

Protection Index	IP20-IP44
Isolation Class	III
Weight [Kg]	13
Country of production	MADE IN ITALY
Mounting instruction	025.494_9010_REV03

Installation

Multisize system	NO
Position	Ceiling

Packaging


Type	White american Box
Measures AxBxH	850x850x300mm
Gross Weight [Kg]	17,443

Master carton	NO
Quantity of articles	
Measures AxBxH	

Technical Data Sheet

4122-4015

Fotometric Data



<i>Electrical part</i>	4015
<i>Power</i>	88W
<i>Light Output</i>	11000lm
<i>Colour Temperature</i>	4000°K
<i>CRI</i>	85
<i>Lamp Light Output</i>	70%
<i>Light Output of the lamp</i>	7700lm
<i>Beam Angle</i>	106°
<i>Beam Inclination</i>	0°

<i>Illuminance</i>	1m	2872lux
	2m	718lux
	3m	319lux
	4m	180lux
	5m	115lux

Accessories

Standard Power Supply


<i>Code</i>	2x026.205
<i>Measures</i>	128x60x31,5mm
<i>Power</i>	min35,7W max59,9W
<i>Input</i>	180-295V~W
<i>Output</i>	1050mA

Dimmable Power Supply

<i>Code</i>	2x026.206.3
<i>Measures</i>	124x82x23mm
<i>Power</i>	59,9W
<i>Input</i>	180-295V~W
<i>Output</i>	1050mA
<i>Dimmable</i>	PUSH/DALI

<i>Code</i>	2x026.207.3
<i>Measures</i>	124x82x23mm
<i>Power</i>	59,9W
<i>Input</i>	180-295V~W
<i>Output</i>	1050mA
<i>Dimmable</i>	0-10V

Other Accessories



<i>Code</i>	099.142
<i>Description</i>	Emergency Kit
<i>Notes</i>	