

Technical Data Sheet

Last data update

3/15/2016

9010
novantadieci®



Req. space behind the plasterboard

100(130*)mm



hole on the plasterboard

525x195mm



External measures

520x190mm



Measures of the light output

460x120mm



Height without electrical part

95mm



Height including the electrical part

100mm

Notes on measures

General notes

INCASSO A PLAFONE E PARETE

4049-4003

Recessed lighting / CRISTALY

Surface finish : CRISTALY

LED 21W / 24Vdc / 2600lm / 4000°K / CRI85

Model

Code	4049
Product family	INCASSO A PLAFONE E PARETE
Type	Recessed lighting

Material/Surface finish

Code	004
Material	CRISTALY
Surface finish	CRISTALY

Electrical part

Code	4003
Type	LED
Power	21W
Tension	24Vdc
Light Output	2600lm
Colour Temperature	4000°K
CRI	85
Light Output of the lamp	1794lm
Dimmable	SI
Power Supply	by Remote Power Supply
Connection	2 PVC cables
Cover	Etched Glass

General Data

Protection Index	IP20
Isolation Class	III
Weight [Kg]	4,3
Country of production	MADE IN ITALY
Mounting instruction	

Installation

Multisize system	NO
Position	Wall lamp/Ceiling Lamp


Packaging

Type	White american Box
Measures AxBxH	600x360x210mm
Gross Weight [Kg]	5,2299
Master carton	NO
Quantity of articles	
Measures AxBxH	

Technical Data Sheet

4049-4003

Fotometric Data




<i>Electrical part</i>	4003_21
<i>Power</i>	21W
<i>Light Output</i>	2600lm
<i>Colour Temperature</i>	4000°K
<i>CRI</i>	85
<i>Lamp Light Output</i>	69%
<i>Light Output of the lamp</i>	1794lm
<i>Beam Angle</i>	73°
<i>Beam Inclination</i>	0°


<i>Illuminance</i>	<i>1m</i>	<i>883lux</i>
	<i>2m</i>	<i>221lux</i>
	<i>3m</i>	<i>98lux</i>
	<i>4m</i>	<i>55lux</i>
	<i>5m</i>	<i>35lux</i>

Accessories


Standard Power Supply




<i>Code</i>	026.259
<i>Measures</i>	167x45x30mm
<i>Power</i>	36W
<i>Input</i>	220-240V~W
<i>Output</i>	24Vdc



<i>Code</i>	026.260
<i>Measures</i>	157x54x36mm
<i>Power</i>	60W
<i>Input</i>	220-240V~W
<i>Output</i>	24Vdc




<i>Code</i>	026.261
<i>Measures</i>	219x63x35.5mm
<i>Power</i>	150W
<i>Input</i>	180-295V~W
<i>Output</i>	24Vdc




<i>Code</i>	026.262
<i>Measures</i>	244x71x35.5mm
<i>Power</i>	240W
<i>Input</i>	180-295V~W
<i>Output</i>	24Vdc


Dimmable Power Supply




<i>Code</i>	026.219
<i>Measures</i>	155x51x26mm
<i>Power</i>	21,6W
<i>Input</i>	220-240V~W
<i>Output</i>	24Vdc
<i>Dimmable</i>	PUSH/0-10V/DALI



<i>Code</i>	026.209
<i>Measures</i>	125x82x29mm
<i>Power</i>	60W
<i>Input</i>	220-240 V~W
<i>Output</i>	24Vdc
<i>Dimmable</i>	PUSH/1-10V




<i>Code</i>	026.190+026.261
<i>Measures</i>	156x52x24mm
<i>Power</i>	150W
<i>Input</i>	180-295V~W
<i>Output</i>	24Vdc
<i>Dimmable</i>	PUSH/0-10V/DALI



<i>Code</i>	026.190+026.262
<i>Measures</i>	156x52x24mm
<i>Power</i>	240W
<i>Input</i>	180-295V~W
<i>Output</i>	24Vdc
<i>Dimmable</i>	PUSH/0-10V/DALI

Other Accessories



<i>Code</i>	099.142
<i>Description</i>	Emergency Kit
<i>Notes</i>	